

ATTENTION: Use this form to determine the proper insurance program and rate. This form is used only to determine the proper insurance program and rate, and or to support a request for a Letter of Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION		FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME	[REDACTED]	POLICY NUMBER
STREET ADDRESS (Including Apt., Unit, Suite and/or Box, P.O. ROUTE AND BOX NUMBER)		COMPANY NAIC NUMBER
OTHER DESCRIPTION (Lot, Block, Subdivision, etc.)		
CITY	STATE	ZIP CODE

SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION *RII 4 Pt. 3701 (5-7-91)*

Provide the following from the proper FIRM (See Instructions):

1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION (in AO Zones, use depth)
065043	0340	B	12-2-80	AO	(1)

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE):  NGVD '29  Other (describe on back)
8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: 1121.2 feet NGVD (or other FIRM datum—see Section B, Item 7).

1213.2 SECTION C BUILDING ELEVATION INFORMATION

1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level: 1
- 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 1121.2 feet NGVD (or other FIRM datum—see Section B, Item 7).
- (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of 1121.2 feet NGVD (or other FIRM datum—see Section B, Item 7).
- (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is 1121.2 feet above  or below  (check one) the highest grade adjacent to the building.
- X (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is 1121.2 feet above  or below  (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance?  Yes  No  Unknown
3. Indicate the elevation datum system used in determining the above reference level elevations:  NGVD '29  Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
4. Elevation reference mark used appears on FIRM:  Yes  No (See Instructions on Page 4)
5. The reference level elevation is based on:  actual construction  construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
- X 6. The elevation of the lowest grade immediately adjacent to the building is: 1210.4 feet NGVD (or other FIRM datum—see Section B, Item 7).

SECTION D COMMUNITY INFORMATION

1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: 1121.2 feet NGVD (or other FIRM datum—see Section B, Item 7).
- X 2. Date of the start of construction or substantial improvement: 10-3-71

Post-It™ brand fax transmittal memo 7671 # of pages 5

To: <u>Gassan</u>	From: <u>Steve Burger</u>
Co.:	Co.:
Dept.:	Phone # <u>805 253-7218</u>
Fax #:	Fax #:

**SECTION E CERTIFICATION**

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, A (with BFE), V1-V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

X  
X

CERTIFIER'S NAME: RAY BOWERS Principal  
 Thomson Property Management Co.  
 LICENSE NUMBER (or Aff. Seal): 444371 CA. Lic. Exp. 1-24-93  
LS 7426 Lic. Exp. 6/30/92

TITLE: 14755 Ventura Blvd Sherman Oaks, Ca. Ca. 91403 COMPANY NAME

ADDRESS: Res. 13901 Olive View Ln 66 Sylmar, Ca. 91342 CITY STATE


SIGNATURE: \_\_\_\_\_ DATE: 10-10-91

Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.


COMMENTS: For Bench Mark to be used in construction contact L.A.Co. Survey Division. Place description below.

CL 4523 Newhall 1982 - EL = 1141.04

3/4 IN NEW SAN IN HORIZIN DN @ C/L INT OF CHIQUITO CN RD & SAN MARTINEZ RD.



NOTE: The Flow Line of the Road at the S.E. Prop. Cor. is 4.8 ft. below Finish Floor elev.



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor. Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.