20 0000

91384

STATE CA

ELEVATION CERTIFICATE FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this cartilicate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances. Io determine the proper insurance premium rate, and/or to support a request for a Later of Map Amendment or Revision (LOMA or LOMF Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION	FOR HEURANCE COMPANY USE
BUILDING OWNER'S NAME	POLICY NUMBER
STREET ADORESS Including Apl. Unit, Sure ender Bing. Humber) GR P.O. ROUTE AND BOX MARLER 30777 Romero Canyon Rd.	COMPANY NAIC MUNICA
OTHER DESCRIPTION is an and Block Magness and I	

Parcel 4, P.M. No. 21144

CITY

Castaic

SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

Provide the following from the proper FIRM (See Instructions):

1. COMMUNITY HUMBER	2. PANEL MUMBER	1. SUFFIX	4. DATE OF PIPM DIDEX	E. FIRM ZONE	4. BASE FLOOD ELEVATION
065043	0340	В	12/02/80	A	

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): XINGVD '29 (C) Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate

SECTION C BUILDING ELEVATION INFORMATION

- 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level
- 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 1151701111 test NGVD (or other FIRM datum-see Section B, Kem 7).
- (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of LILL LI test NGVD (or other FIRM datum-see Section B, Item 7).
- (c). FIRM Zone À (withour BFE). The floor used as the reference level from the selected diagram is 12. 1 feet above a or below (check one) the highest grade adjacent to the building.
- (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is LLL. feet above a or below (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? Yes No (Unknown
- 3. Indicate the elevation datum system used in determining the above reference level elevations: ... NGVD '29 ... Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM (see Section B, Item 7), then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
- 4. Elevation reference mark used appears on FIRM: Ves No (See Instructions on Page 4)
- 5. The reference level elevation is based on: actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
- 6. The elevation of the lowest grade immediately adjacent to the building is: 115 [618].10].teet NGVD (or other FIRM datum-see Section B, tem 7).

SECTION D COMMUNITY INFORMATION

1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C. Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest

floor" as defined by the ordinance is: <u>| | | | | |</u> feet NGVD (or other FIRM datum-see Section B, Item 7). 2. Date of the start of construction or substantial improvement <u>| | | 01 98</u> 6 7

FEMA Form \$1-31, MAY 93

REPLACES ALL PREVIOUS EDITIONS

SEE REVERSE SIDE FOR CONTINUATIC

SECTION & CERTIFICATION

۰.

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, A (with BFE), V1-V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide Bodplain management information, may also sign the certification.

Reference level diagrams 6.7 and 8 - Distinguishing Features—If the certifier is unable to certify to breakaway/non-breakaway wall, unclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not uncluded in the certification under Comments below. The diagram number, Section C, item 1, must still be entered.

I certily that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any laise statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME	Noville		19740	er Allit Bood	
TITLE	NOVILLE	COMPANY NAM	19740		
Civil	Engineer				
ADORESS		CITY		STATE	29
27959	Featherstar Ave.	Saugus		CA	91350
SIGNATURE	Mmelo		0ATE 12/08/98	(805) 296-8027	
Copies should i	be made of this Certificate for	: 1) community officia	ui, 2) insurance ag	jent/company, and 3) buil	ding owner.
COMMENTS:	Bench Mark used was	the Los Angeles	County Depar	tment of Public Wo	rks
	BM CY4562, Newhall (uad (1993 Adjust	ment)		
	Reference Los Angele	s County Departm	ent of Publi	c Works ROMERO CAN	YON
	Floodway Map No. 388	-ML7		OFFESSION	
				ASED TH 410	City .
·				3 3	NEXO
				197100	nt t
	CH CH	WTH	•	A A A A A A A A A A A A A A A A A A A	ANIT .
			•	MENTE ON COLUMNIA C	0.
1	tones gones	TT ZONES		20146 20146	নি
MITTALICE					- Inventer
		Щ	R COD R PARQU		
			mulun	- medium	\
		TOTAL TOL Y			
	AVENUEL HONEUT		- WM		A States
	Criter - ever		4	NW	N
			ſ		
	•				ADMCANT
	·			and the second second	
The diagra	ams above illustrate the points a	It which the elevations	should be measure	d in A Zones and V Zones.	_
Elevations	for all A Zones should be mee	turad at the ten of the o			•
- Elouation					