

593-117



FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ELEVATION CERTIFICATE

This form is to be used for: 1) New/Emergency Program construction in Special Flood Hazard Areas; 2) Pre-FIRM construction after September 30, 1982; 3) Post-FIRM construction; and, 4) Other buildings rated as Post-FIRM rules.

UILDING OW	NER'S				ADDRESS					
IAME							•	w.		
ROPERTY LC	CÁTION (L	ot and Blo	ck numbers	and addres	s if available)	.^				_
101.	42	an I	Franc	SISAU	ito CVI	ı Kd	- Gre	en 1	Calley, CA	91.
					y best efforts to in					
•		•	•		18 U.S. code, See		ficial or a Regis	tered Pr	ofessional Engin	eer.
				chitect, or S						
OM YTINUMMO	PANEL NO.	SUFFIX	DATE OF FIR	M FIRM ZO	NE DATE OF CONS	TR. BASI	E FLOOD ELEV Zone, use depth)	BUILDIN	IG IS	
4/-240	0000	R	100	ν Π	·	. '	1		Pre-FIRM Re	9.
165045	0205	D_{-}	12-1-1	$U \square$	1785		,			
ord	dinance. The	certifier r	nay rely on . Failure to	community construct th	will be constructed records. The lowe e building at this conse	est floor (in-	cluding basem	ent) will	be at an elevati	on
(ES NO The	e building d	escribed and on elev	bove has be	een construction	cted in compliance spection or other i	reasonable	ommunity's flo means.	ood plair	n management	d
ES NO Th	e mobile ho mmunity's fi	ne locate	d at the add managemer	ress describ	ed above has bee	n tied dowi	n (anchored) in	n compli	ance with the	. •:
	HOME MAKI		MODEL		YR. OF MANUFAC		SERIAL I		. DIMENSION	s
	1.2				k Karananan kan				χ.	
						- C	<u> </u>			لــــ
IAME BO		To	ICY	essional Eng	ineer, Architect, o	11.10	WAV	1	Congression	<u>.</u>
ITLE CIV	ill En	GINCE	$r \mathcal{I}_{ ext{cut}}$	Lan	caster	s	TATE CQ	·	ZIP 95	<u>55</u>
	77		/		11) / <i> </i> 13/£	(,	795	945-60	11
IGNATURE	Ba	Wil	(-/(elei	\sim nate ld	~/ /.//U	JPHONE ()			11
	Ba	M	CATION (Certified by	DATE /	ty Permit O	JPHONE ()	istered F	Professional Engi	neer.
	A1-A30: I d	ertify that	the building	g at the pro	perty location des NGVD (mean sea	cribed abov	ve has the low	est floor	(including baser	nent)
SECTION II	A1-A30: I c at an	ertify that an elevation elevation I certify at an el	the building of that the building evation of	g at the pro	perty location des NGVD (mean sea 3VD. property location of feet, NGVD (mean	cribed above level) and	ve has the lower the average of	est floor grade at	(including baser the building site	nent) is.at
SECTION II	A1-A30: I c at an	ertify that an elevation elevation I certify at an el	the building of that the building of the build	g at the pro	perty location des NGVD (mean sea 3VD.	cribed above level) and	ve has the lower the average of	est floor grade at	(including baser the building site	nent) is.at
FIRM ZONE	A1-A30: i c at an	ertify that an elevation I certify at an el is at an	the building of that the building of that the building of elevation of the second of t	g at the pro	perty location des NGVD (mean sea 3VD. property location of feet, NGVD (mean feet, NGVD.	cribed above a level) and described a n sea level)	ve has the lower the average of the bove has the box, and the average of the aver	est floor grade at ottom of age grad	(including baser the building site the lowest floor is at the building	nent) is at beam g site
FIRM ZONES	A1-A30: i c at an 3 V, V1-V30: A, A99, A0 ha	ertify that an elevation I certify at an el is at an O, AH, and s the lowe	the building of that the building of that the building of the elevation of	g at the pro- feet, feet, No Iding at the	perty location des NGVD (mean sea 3VD. property location of feet, NGVD (mean feet, NGVD.	cribed above a level) and described an sea level) the building.	we has the lower the average of the average of the average of the average of the properties of the properties of the average of the average at the properties are average of the average of t	est floor grade at ottom of age grade erty loca erty loca a highes	(including baser the building site the lowest floor de at the building ation described a at adjacent grade	nent) is at beam g site
FIRM ZONES	A1-A30: I c at an	ertify that an elevation I certify at an el is at an O, AH, and s the lowe the buildi OOFING y knowled neable to and effect	the building of that the building of that the building of elevation of the state of the state of the state of the passage to of buoyar	g at the project, feet, No. 1 dding at the NCY PROGE vation of 3 feet, 1 dding at the state of water in the of water in the project of the of water in the original water	perty location des NGVD (mean sea 3VD. property location of feet, NGVD (mean feet, NGVD.	cribed above a level) and described an sea level) the building SVD. The existence Produing is deal apponents had a level apponent had a level	bove has the low, and the average of	est floor grade at ottom of age grad erty loca e highes	(including baser the building site the lowest floor ide at the building atton described a tradjacent grade Architect)	beambove next
IRM ZONES IRM ZONES IRM ZONES ECTION III certify to the valis subtate and hydrodyrorces associated.	A1-A30: I c at an	l certify that an elevation levation le	the building of that the building of that the building of elevation of the set floor elevation of the pass of the passages of buoyand of flooding ervention means of the passages of the passa	g at the project, feet, No. Get, No. Iding at the ground of the ground	perty location des NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. property location of feet, NGVD. RAM: I certify that OI3-9 feet, NGVD. ification by a Regional structural conclude be caused by the gree of floodproopers will enter the least of the sea GVD.	cribed above a level) and described an sea level) the building and the flood ding be ach building who building who building who a level and the flood ding be ach building who are the flood ding be ach building who	the average of the av	est floor grade at ottom of age grade erty loca e highes neer or A he build ability o es veloc nan inte	(including baser the building site the lowest floor deat the building at adjacent grade architect) ling is watertight f resisting hydroitles, impact and rvention?	bove nex
IRM ZONES	A1-A30: I c at an	l certify that an elevation l certify at an elevation l certify l certify at an elevation l certification l certificat	the building of that the building of that the building of the	g at the project, or feet, No. feet,	perty location des NGVD (mean sea NGVD) property location of feet, NGVD (mean sea NGVD) property location of feet, NGVD. RAM: I certify that OI3-9 feet, NGVD. RAM: I certify that oil feet, NGVD.	cribed above a level) and described an sea level) the building and the flood ding be ach building who building who building who a level and the flood ding be ach building who are the flood ding be ach building who	the average of the av	est floor grade at ottom of age grade erty loca e highes neer or A he build ability o es veloc nan inte	(including baser the building site the lowest floor deat the building at adjacent grade architect) ling is watertight f resisting hydroitles, impact and rvention?	beambove bove bove next
IRM ZONES	A1-A30: I c at a an a	ertify that an elevation an elevation levation l	the building of that the building of that the building evation of elevation of the set floor elevation of the passage of buoyand of the passage of buoyand of the passage ervention measures arwindows). Iding be occ	g at the property of the prope	perty location des NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. property location of feet, NGVD. RAM: I certify that OI3-9 feet, NGVD. ification by a Regional structural conclude caused by agree of floodproof ter will enter the rothe flood to presidence? annot be credited	cribed above a level) and described an sea level) the building VD. The existered Profiling is designated building wherevert entry for rating g	bove has the lowing the average of t	est floor grade at ottom of age grad erty loca a highes he build ability o es veloc nan inte o the ba	(including baser the building site the lowest floor is at the building at the building at adjacent grade architect) ling is watertight fresisting hydrotitles, impact and rvention? use flood level oc grade shields o	beam bove next
IRM ZONES	A1-A30: I c at an	l certify that an elevation l certify at an el is at a	the building of that the building of that the building of elevation of elevation of the state of the state of the passage to fooding the passage to fooding the passage of the passage of the passage to fooding the passage of the the pas	g at the project, or feet, No. 1 feet, No. 2 feet, No.	perty location des NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. RAM: I certify that Old feet, NGVD. RAM: I certify that Old	cribed above a level) and described and sea level) the building and isstered Proposition is designed and in the flood ding be ach building wherevent entry for rating a ing certifical and a level an	bove has the lowing the average of t	est floor grade at ottom of age grade erty locate highes heer or A he build ability o es veloc nan inte o the ba he botting	(including baser the building site the lowest floor is at the building at the building at adjacent grade architect) ling is watertight fresisting hydrotitles, impact and rvention? use flood level oc grade shields o	beambeambove bove bove next
IRM ZONES	A1-A30: I c at a an a	l certify that an elevation elevation l certify at an el is at an	the building of that the building of that the building of the	g at the pro- get, No. Get, No. Iding at the NCY PROGF vation of 3 Feet, TION (Cert attion, and be e of water a ncy that wo e taken prio cupied as a odproofing on the elevation	perty location des NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. RAM: I certify that Old feet, NGVD. RAM: I certify that Old	cribed above a level) and described and sea level) the building VD. The existered Profing is designated and fing be ach building wherevent entry ing certificatified Floodparts and search	the average of the av	est floor grade at ottom of age grade erty locate highes heer or A he build ability o es veloc nan inte o the ba he botting	(including baser the building site the lowest floor de at the building atton described at adjacent grade architect) ling is watertight f resisting hydrotitles, impact and revention? see flood level on grade at lowest floor metal shields of all lowest floor metals and all lowest fl	beambove next
FIRM ZONES	A1-A30: I c at a and a a	l certify that an elevation elevation l certify at an el is at an	the building of that the building of that the building of the	g at the property of the prope	perty location des NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. RAM: I certify that ONGVD. RAM: I certify that ong the feet, NGVD. RAM: I certify the feet, NGVD. RAM: I certify the feet, NGVD. RAM: I certify	cribed above a level) and described and sea level) the building VD. The existered Profing is designated and fing be ach building wherevent entry ing certificatified Floodparts and search	the average of the av	est floor grade at ottom of age grade erty loca a highes neer or A he build ability o es veloc nan inte o the ba bolting	(including baser the building site the lowest floor de at the building atton described at adjacent grade architect) ling is watertight f resisting hydrotitles, impact and revention? see flood level on grade at lowest floor metal shields of all lowest floor metals and all lowest fl	beambove next
IRM ZONES	A1-A30: I c at a and a a	ertify that an elevation elevation I certify at an elis at an eli	the building of that the building of that the building of the	g at the property of the prope	Surveyor.) perty location des NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. property location of feet, NGVD. RAM: I certify that O13-9 feet, NGVD. Gram: I certify that the build and structural conclude be caused by gree of floodproof atter will enter the rothe flood to presidence? annot be credited on and floodproof Certify SECTIONS II AN	cribed above a level) and described and sea level) the building VD. The existered Profing is designated and fing be ach building wherevent entry ing certificatified Floodparts and search	the average of the av	est floor grade at ottom of age grade erty loca a highes neer or A he build ability o es veloc nan inte o the ba bolting	(including baser the building site the building site the building at the building at the building at adjacent grade architect) ling is watertight fresisting hydrotites, impact and revention? se flood level oc grade shields of the building at the building at the building architect.	bove next upili
IRM ZONES	A1-A30: I c at a and a a	ertify that an elevation elevation I certify at an elis at an eli	the building of that the building of that the building evation of elevation of elevation of the set floor elevation of the set floor elevation of the passage to flooding envention measures arwindows). Iding be occurrent to the passage of the flooding be occurrent to the passage to flooding be occurrent to the passage of the flooring between the passage of the passage o	g at the project. Seek, No. 19 PROGE VALUE OF THE WAY O	perty location des NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. RAM: I certify that OI3-9 feet, NGVD.	described above a level) and described and d	the average of the av	est floor grade at ottom of age grade erty loca a highes neer or A he build ability o es veloc nan inte o the ba bolting	(including baser the building site the building site the building at the building at the building at adjacent grade architect) ling is watertight fresisting hydrotites, impact and revention? se flood level oc grade shields of the building at the building at the building architect.	bove next upili
IRM ZONES IRM ZO	A1-A30: I c at an	ertify that an elevation elevation I certify at an elis at an eli	the building of that the building of that the building evation of elevation of elevation of the set floor elevation of the set floor elevation of the passage to flooding envention measures arwindows). Iding be occurrent to the passage of the flooding be occurrent to the passage to flooding be occurrent to the passage of the flooring between the passage of the passage o	g at the project. Seek, No. 19 PROGE VALUE OF THE WAY O	perty location des NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. RAM: I certify that Olay feet, NGVD. RAM: I cer	described above a level) and described and d	the average of the av	est floor grade at ottom of age grade erty loca a highes neer or A he build ability o es veloc nan inte o the ba bolting	(including baser the building site the building site the building site at the building at the building site at the building site adjacent grade architect) sing is watertight fresisting hydrotitles, impact and resisting hydrotitles.	bove next upili
IRM ZONES IRM ZO	A1-A30: I c at an	ertify that an elevation elevation I certify at an elis at an eli	the building of that the building of that the building evation of elevation of elevation of the set floor elevation of the set floor elevation of the passage to flooding envention measures arwindows). Iding be occurrent to the passage of the flooding be occurrent to the passage to flooding be occurrent to the passage of the flooring between the passage of the passage o	g at the property of the prope	perty location des NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. property location of feet, NGVD (mean sea GVD. RAM: I certify that OI3-9 feet, NGVD.	cribed above a level) and described and sea level) the building VD. The existered Profile is destinated in sea level) the flood of the	bove has the lowing the average of the average of the average of the property of the average of	est floor grade at option of age grade a highes neer or A he build ability o es veloc nan inte o the ba., bolting the actual on is 300 LICENS	(including baser the building site the building site the building at the building at the building at adjacent grade architect) ling is watertight fresisting hydrotites, impact and revention? se flood level oc grade shields of the building at the building at the building architect.	beam j site bove nex with stati upil