

200
100
100
100

16

152
778
975
10078

copy

7850

FIELD NOTES

TOWNSHIP TWO SOUTH

RANGE NINE WEST

SECTIONS, 31, 32, 33, 34

35 and 36

and

TOWNSHIP THREE SOUTH

RANGE NINE WEST

SECTIONS 1, 2, 3, 4, 5,

and 6

S. B. M.

R.9.W.

230	29	28	27	26	25	
231	7 32	7 733	6 634	6 635	536	31
3 6	5 5	5 114	5 103	4 92	4 81	
7	12 8	11 9	10 1010	9 911	8 812	

T.2.S.

T.3.S.

EXTERIORS

T. 2 and 3 S., R. 9 W., East Boundary

South on the West boundary of section 31, T. 2 S., R. 8 W. S.B.M.

- 4.00 Cross arroyo with little water, course S. 40° W.
 - 12.00 Cross arroyo 150 lks. wide, course N. 60° W.
 - 19.00 Ravine N. 33° W.
 - 27.18 Ravine N. 33° W
 - 35.50 Westerly slope of ridge
 - 39.70 Gulch, course SW
 - 40.00 Set $\frac{1}{2}$ section post and charred stake in rocky mound
 - 45.00 Spur
 - 47.25 Gulch S. 20° W.
 - 48.25 Gulch S. 30° W.
 - 50.00 Ravine S. 32° W.
 - 60.00 Leave Chamisal and enter Wild Oats
 - 72.50 Top of ridge, course East
 - 80.00 Set Tp. corner post to Tps. 2 and 3 S., Rgs. 8 and 9 W and charred stake in mound
- finding it impossible to measure but a short distance
I commence to the SW corner of the Tp. and measure
East on the South boundary of sections 31
- 8.00 Enter Chamisal
 - 10.00 Center of ravine, course N. 60° W.
 - 15.00 North slope
 - 18.20 Set Post and charred stake on East face of an insuperable ravine ranging N. 54° W.

From which bears an

Oak S. 86 $\frac{1}{2}$ ° W., 247 lks.

Oak 281 lks. NW

West on the South boundary of section 36 from the corner of Tp. 2 and 3 S., Rgs. 8 and 9 W.

- 1.00 Enter Wilde Sage
9.00 Point of spur
13.00 Ravine N. 37° W.
16.75 Ridge
18.00 Ravine
22.00 Ridge and trail N. 2° W. and leave wilde Oats
30.00 To spur on face of ravine taking to Canada, course S. 35° W., set post with charred stake in an irregular mound with pits on E and W.

The insuperable roughness rendering it impossible to measure further with any due degree of accuracy.

---0---

South on the East boundary of section 1 from the corner of Tp. 2 and 3 W., Rgs. 8 and 9 W.

- 7.00 To point of ridge commanding a view of an exceedingly deep and insuperable ravine on South. Being unable to pursue this line further I set a post and charred stake in an irregular mound with pits on N and S side.

---0---

West boundary of Tp. 2 and 3 S., R. 9 W.

- 72.80 S. on W. boundary of section 30
To witness corner to section ~~30~~ and 31 on bank of insuperable ravine

Thence at

- 80.00 Set section post and charred stake in mound 7.20 chs. N. of true corner.

---0---

S. on W. boundary of section 31 not being able to measure South from witness corner to sections 30 and 31 I proceed to a point due South (on a ridge ranging E and W) and take a base to the W. 250 lks. from which a fire built on a witness mound aforesaid bears N. 5° 50' E.

Through fog and at 700 lks. W. on same base N. 16° E. giving dist. from witness mound to point on ridge on the South (by right angle triangulation) 23.85 lks. — after which by measuring N. from said triangulation point as far as practicable and find the distance 2 chs.

(calc)
24.45
End of 260

South from true corner to sections 30 and 31

- 16.65 To ridge ranging E and W
- 19.65 To gulch of ravine
- 36.15 To top of South slope of ridge, course S. 65° E.
- 40.00 Too steep for corner post
- 44.15 Ravine, course S. 22° E.
- 45.15 Set 1/2 section post in witness mound of rock and earth
Pits N and S/
- 55.00 Gulch with dense thickets
- 58.00 East slope of ridge
- 61.00 Deep gulch
- 70.00 South slope of ridge
- 80.00 Set Tp. post and charred stake in mound corner to Tp. 2 and 3 S., Rgs. 9 and 10 W.,
Hilly soil, first rate. Wild Oats.

(6)

---O---
TOWNSHIP BOUNDARY T. 2 S., R. 9 W., S.B.M.

In measuring East as far as possible on the South boundary of T. 2 S., R. 9 W. I make the following notes:

East on the South boundary of section 31

- 6.00 To deep gulch
- 9.00 Arroyo of ravine or valley 6 lks. over ranging S. 45 1/2° E. valley over 2 chs. wide.
- 11.36 To post at the base of an inaccessible and high mountain on the East of valley,

396

574

(7) 750

From which bears a

Walnut 18 in. dia. N. 1 1/2° W., 19 lks.

Walnut 5 in. dia. S. 4 1/2° W., 67 lks.

---O---

South on the West boundary of section 6

- 7.00 To trail at the base of a hill
- 10.50 Arroyo 6 lks. wide, dry, course S. $43\frac{1}{2}^{\circ}$ W.
- 11.50 Point of sharp ridge
- 12.00 Steep gulch
- 21.00 Ravine, course West
- 40.00 Set $\frac{1}{4}$ section post and charred stake in mound (8)
- 54.00 To arroyo canada La Brea
- 59.00 In open La Brea Spring at base of S. face of the Canada
- 62.00 Leave the La Brea
- 67.00 Top of bluff
- 70.00 Ravine
- 80.00 Set section post and charred stake in mound on South (9)
side of hill corner to sections 6 and 7.
Land hilly. Soil second rate. Good pasturage.

---0---

LINE BETWEEN Tps. 2 and $\frac{3}{4}$ South, RGS. 9 W. S.B.M.

From post previously established on Line on South
boundary between sections 1 and 36.

30 chs. W. of corner to Tp. 2 and 3 S., Rgs. 8 and 9 W.
counting from said tp. corner I run

West on a true line on the South boundary of Tp. between
sections 1 and 36.

Var. $13^{\circ} 25'$ East.

- 40.00 Set a rock 20 x 12 x 6 in. for $\frac{1}{4}$ section corner (10)
- 66.50 Cross stream of water 10 lks. wide, course SW
- 80.00 Set post for corner to sections 1, 2, 35 and 36 in (11)
mound with trench and pits as per instructions.
Land mountainous and broken. Covered with sage.

---0---

West between sections 2 and 35

Var. $13^{\circ} 25'$ East.

- 40.00 Set s sand stone 16 x 10 x 7 for $\frac{1}{4}$ section corner (12)
- 80.00 Set a gray sand stone 16 x 14 x 5 for corner to sections (12)

2, 3, 34 and 35.

Land mountainous. Soil second rate

---0---

West between sections 3 and 34.

Var. 13° 25' East.

40.00 Set a brown sand stone 15 x 12 x 8 for 1/4 section corner

80.00 Set sand stone 15 x 10 x 8 for corner to sections 3, 4, 33 and 34

Land mountainous. Soil second rate.

---0---

West between sections 4 and 33

Var. 13° 25' East

40.00 Set a brown sand stone 14 x 12 x 10 for 1/4 section corner.

80.00 Set rock 24 x 15 x 6 for corner to sections 4, 5, 32 and 33.

Land very broken and mountainous. Soil third rate.

---0---

West between sections 5 and 32

Var. 13° 25' East.

40.00 Set sand stone 18 x 12 x 4 for 1/4 section corner

80.00 Set gray sand stone 21 x 9 x 6 for corner to sections 5, 6, 31 and 32.

Land mountainous. Soil second rate.

---0---

WEST BETWEEN SECTIONS SIX AND THIRTY ONE

NOT RUN BECAUSE OF EXTREME ROUGHNESS AND FALLING INSIDE OF A RANCHO.

---0---

Subdivisions of T. 2 S., R. 9 W.

North between sections 35 and 36

Var. 13° 25' East.

40.00 Set 1/4 section corner post in mound with trench and pits

(13)

(14)

(15)

(16)

asper instructions on South boundary line of Rancho Santa Anadel Chino 40 chains East of the SW corner of said Rancho.

Land hilly Soil second rate.

---0---

North between sections 34 and 35

Var. 13° 25' East.

40.00 Set $\frac{1}{4}$ section post in mound with trench and pits as per instructions.

80.00 Set post for corner to sections 26, 27, 34 and 35 in mound with pits and trench as per instructions on South bluff of Canada La Brea.

Land broken and hilly. Soil second rate.

---0---

East between sections 26 and 25

Var. 13° 25' East

40.00 Set $\frac{1}{4}$ section post in mound with trench and pits as per instructions on West boundary of Rancho Santa Anadel Chino 40 chains N. of the SW corner of same.
Land hilly. Soil second rate.

---0---

North between sections 33 and 34.

Var. 13° 25' East.

40.00 Set Gray sand rock 14 x 12 x 6 for $\frac{1}{4}$ section corner

80.00 Set rock 14 x 12 x 8 for corner to sections 27, 28, 33 and 34.

Land hilly. Soil second rate.

---0---

East on a random line between sections 27 and 34.

Var. 13° 25' East.

40.00 Set temporary $\frac{1}{4}$ section post

72.00 Cross Canada La Brea 3 chains wide, course SW

80.20 Intersect the N and S line 30 lks. N. of the corner to sections 26, 27, 34 and 35,

From which corner I run

W. on a true line between sections 27 and 34.

17

18

19

20

Var. 13° 25' East.

40.10 Set 1/4 section post in mound with trench and pits as per instructions

(21)

80.20 To corner to sections 27, 28, 33 and 34.
Land hilly. Soil second rate.

---0---

North between sections 32 and 33

Var. 13° 25' East

40.00 Set sand stone rock 14 x 13 x 8 for 1/4 section corner

80.00 Set granite rock 14 x 8 x 6 for corner to sections 28, 29, 32 and 33.

(22)

Land broken. Soil second rate.

---0---

East on a random line between sections 28 and 33

Var. 13° 25' East.

40.00 Set rock for temporary 1/4 section corner.

48.00 Enter canada

58.50 Cross same, course S. 60° W.

(23)

80.00 To corner to sections 27, 28, 33 and 34

From which corner I run

West on a true line between sections 28 and 33.

var. 13° 25' East.

40.00 Set granite stone 20 x 10 x 4 for 1/4 section corner

80.00 To corner to sections 28, 29, 32 and 33

Land hilly. Soil second rate.

---0---

From the corner to sections 28, 29, 32 and 33 I run

West between sections 29 and 32

Var. 13° 30' East.

40.00 Set rock 20 x 10 x 4 for 1/4 section corner

80.00 Set sand stone rock 12 x 10 x 11 for corner to sections

(24)

29, 30, 31 and 32 on West side of valley 22 chs. N. of post

No. 5 of Rancho De La Brea. Land undulating second rate.

22
56
1332
1452

Subdivisons T. 3 S., R. 9 W.

North between sections 11 and 12.

Var. 13° 25' East

80.00

Set post for corner to sections 1, 2, 11 and 12

Drove charred stake and raised mound with trench and pits as per instructions.

Land hilly. Soil second rate.

---0---

East on a random line between sections 1 and 12.

Var. 13° 25' East.

40.00

Set post for temporary $\frac{1}{4}$ section corner

79.90

Intersect the East boundary of Tp. 25 lks. N. of corner to sections 1, 2, 6 and 7

From which corner I run

N. 89° 50' W. on a true line between sections 1 and 12.

Var. 13° 25' East

39.95

Set post for $\frac{1}{4}$ section corner, drove charred stake and raised mound with trench and pits as per instructions.

79.90

To post corner to sections 1, 2, 11 and 12.

Land hilly. Soil second rate.

---0---

North on a random line between sections 1 and 2

Var. 13° 25' East.

40.00

Set post for temporary $\frac{1}{4}$ section corner

79.50

Intersect the North boundary of Tp. 40 lks. E. 55 post corner to sections 1, 2, 35 and 36

From which corner I run

S. 17° E. on a true line between sections 1 and 2

Var. 13° 25' East.

17.00

Cross stream of water 10 lks. wide flowing thru the canyon SW.

39.50

Drove post and charred stake for $\frac{1}{4}$ section corner.

25

26

27

From which bears an
Oak 10 in. brs. N. $7\frac{1}{2}^{\circ}$ E., 153 lks. 101.0
Oak 10 in. brs. N. 29° W., 206 lks. 136.
79.50 To corner to sections 1, 2, 11 and 12.
Land undulating. Soil second rate.
---0---
North between sections 10 and 11.
Var. $13^{\circ} 25'$ East.
80.00 Set sand stone rock 16 in. X 12 X 5 in. for corner
to sections 2, 3, 10 and 11 and marked same as per
instructions
Land hilly. Soil second rate.
---0---
East on a random line between sections 2 and 11
Var. $13^{\circ} 25'$ East.
19.00 Stream of water 10 lks. wide, course SW
40.00 Set rock for temporary $\frac{1}{4}$ section corner
80.70 Intersect the N and S line at post corner to sections
12, 11, 1 and 2
From which corner I run
W. on a true line between sections 2 and 11.
Var. $13^{\circ} 25'$ East.
40.35 Set a sand stone rock 14 in. long, 12 in. wide, and
9 in. thick for the $\frac{1}{4}$ section corner and marked same
as per instructions.
80.70 To corner to sections 2, 3, 10 and 11
Land hilly. Soil second rate.
---0---
North on a random line between sections 2 and 3
Var. $13^{\circ} 25'$ East.
40.00 Set a post for temporary $\frac{1}{4}$ section corner
79.49 Intersect the North boundary of Tp. 12 lks. E. of the
corner to sections 2, 3, 34 and 35,

27

28

29

From which corner I run

S. 5' E. on a true line between sections 2 and 3.
 Var. 13° 25' East.

39.49 Set a post and charred stake in mound for $\frac{1}{4}$ section corner with trench and pits as per instructions.

79.49 To corner to sections 2, 3, 34 and 35
 Land hilly. Soil second rate.

--O--

North between sections 9 and 10.
 Var. 13° 25' East.

40.00 Set a sand stone 18 x 14 x 6 for the $\frac{1}{4}$ section corner and marked same as per instructions.

80.00 Set a gray sand rock 13 x 13 x 8 for corner to sections 3, 4, 9 and 10 on South slope of hill, marked same as per instructions.
 Land hilly. Soil third rate.

--O--

East on a random line between sections 3 and 10.
 Var. 13° 25' East.

40.00 Set temporary $\frac{1}{4}$ section corner

80.08 Intersect the N and S line at post corner to sections 2, 3, 10 and 11

From which corner I run

West on a true line between sections 3 and 10.
 Var. 13° 25' East.

40.04 Set sand stone 13 x 10 x 6 for $\frac{1}{4}$ section corner marked same as per instructions.

80.08 To corner to sections 3, 4, 9 and 10.
 Land hilly. Soil second rate.

--O--

North on a random line between sections 3 and 4.
 Var. 13° 25' East.

40.00 Set a post for temporary $\frac{1}{4}$ section corner.

30

31

32

79.50 Intersect the North boundary of Tp. 40 lks. E. of the corner to sections 3, 4, 33 and 34

From which corner I run
S. 17' E. on a true line between sections 3 and 4.

Var. 13° 25' East.

39.50 Set a post for $\frac{1}{2}$ section corner Drove charred stake and raised mound with trench and pits as per instructions

79.50 To corner to sections 3, 4, 9 and 10.

Land hilly. Soil second rate.

---O---

North between sections 8 and 9

Var. 13° 25' East.

80.00 Set a sand rock 18 x 9 x 9 for corner to sections 8, 9, 4 and 5 and marked same as per instructions. Land hilly and second rate.

---O---

East on a random line between sections 4 and 9.

Var. 13° 25' East.

40.00 Set temporary $\frac{1}{2}$ section corner

80.00 Intersect the N and S line at post corner to sections 3, 4, 9 and 10

From which corner I run

West on a true line between sections 4 and 9.

Var. 13° 25' East.

40.00 Set sand stone 15 x 10 x 6 in. for $\frac{1}{2}$ section corner marked same as per instructions.

80.00 The post corner to sections 4, 5, 8 and 9

Land hilly. Soil second rate.

---O---

North on a random line between sections 4 and 5.

Var. 13° 25' East.

40.00 Set post for temporary $\frac{1}{2}$ section corner

79.40 Intersect the N boundary of Tp. 80 lks. ^W of the corner

to sections 4, 5, 33 and 38

From which corner I run

S. 34° W. on a true line between sections 4 and 5

Var. $13^{\circ} 25'$ East.

39.40 Set a sand stone 25 x 10 x 7 for $\frac{1}{4}$ section corner

79.40 To corner to sections 4, 5, 8 and 9

Land hilly. Soil second rate.

---O---

West on a true line between sections 5 and 8

Var. $13^{\circ} 25'$ East.

40.00 Set a rock 18 x 8 x 5 for $\frac{1}{4}$ section corner

53.60 Intersect the East boundary of the Ranch Cajon De
San Juan 13.60 chains W. of the $\frac{1}{4}$ section corner and
13.50 chs. S. $5\frac{1}{2}^{\circ}$ E. of a Live Oak.

Station No. 3 of Rancho Canada Le Brea

Land broken. Soil second rate.

HENRY HANCOCK

1858

---O---

36

37