

FIELD NOTES.

Township 1 N, Range 10 W.

S. B. H.

East Line Sec. 26
 East Line Sec. 23
 West Line Sec. 23
 South Line Sec. 23
 North Line Sec. 23
 South Line Sec. 22
 West Line Sec. 22
 North Line Sec. 22
 West Line Sec. 15
 North Line Sec. 15

		R 10 W T 2 N							
		6	5	4	3	2	1		
		7	8	9	10	11	12		
		18	17	16	15	14	13		
TIN		19	20	21	22	23	24	TIN	
		30	29	28	27	26	25		
		31	32	33	34	35	36		
		R 10 W							

Norway 1875

T 1 N, R 10 W, S. B. M.

NORTH between Sections 25 and 26.

East point Argusa Rancho.

Var. $14\frac{1}{4}^{\circ}$ E.

80 00 Set an Oak post 3 x 3 in., and 3 ft. long in rock mound, as instructed, on steep side hill facing West for corner to Sections 23, 24, 25 and 26.

Land mostly level, 1st. rate.

North between Sections 23 and 24.

Var. $14\frac{1}{4}^{\circ}$ E.

Ascend abrupt mountain.

40 00 Set Redwood post 3 x 3 in., 3 ft. long in a mound of rocks, as instructed, for $\frac{1}{4}$ section corner on side hill facing South.

50 00 Summit of spur, course SW and E.

60 00 Enter valley of San Gabriel River.

61 50 San Gabriel River 50 lks wide, course NW.

72 50 San Gabriel River 50 lks wide, course SE.

76 00 Enter field, course NW and SE.

80 00 Set Sycamore post 4 x 4 in., 3 ft. long in large mound of rocks, as instructed, for corner to sections 13, 14, 23 and 24, in center of small field, a house bears S. 64° E. about 7 chs. distant.

Land rough, with scattering timber, 2nd. and 3rd. rate soil.

November 27, 1875.

From the corner to Sections 23, 24, 25 and 26, I run

WEST on a true line between Sections 23 and 26.

Var. $14\frac{1}{4}^{\circ}$ E.

16 50 Cross gulch, course S.

40 00 Set Oak post 3 x 3 in., 3 ft. long in mound of rocks on summit of ridge, course NE & SW, as instructed, for $\frac{1}{4}$ section corner, thence descend.

46 00 Cross a ravine 50 lks. wide, course SW.

50 00 Summit of a spur, course N. & S. and descend.

52 00 Cross ravine, course S. A spring about 5 chs. N.

67 00 To dry ravine.

68 00 Over same, course SW.

74 25 Descend steep bluff into valley of San Gabriel, course N & S.

80 00 Set an Alder post 4 x 4 in., 3½ ft. long in a mound of rocks, as instructed, for corner to sections 22, 23, 26 and 27.

Land mostly along foot hills, 1st. and 2nd rate.

NORTH between Sections 22 and 23.

Var. 14¼° E.

19 00 To edge of high rocky point too rough to measure, I offset West 5 00 chains to valley, thence N. 15 00 chs. Henry Robert's house W. of line, 31 22 chs. to N. point of hill; thence East 5 00 chains to line between sections 22 and 23. 10 22 chains North of ¼ section corner at an Alder tree 2 ft. dia., I marked for witness to ¼ section corner, on NE edge of Sanja, course SW. thence continue NORTH between sections 22 and 23.

50 50 Counting the distance from the corner to sections 22, 23, 26 and 27, cross wagon road, course SW. & NE.

55 30 Cross San Gabriel River 50 lks. wide, course SW.

62 50 Leave river West and ascend steep side hill, course E & W.

77 40 Edge of steep side hill I set an Alder post 4 x 4 in., 3½ ft. long in a mound of rock, as instructed, for witness to corner to Sections 14, 15, 22 and 23, as the true corner will fall on steep side hill, not a suitable place to build a monument.

80 00 Point for corner to Sections 14, 15, 22 and 23.

Land along river 2nd. and 3rd. rate.

EAST on a random line between Sections 14 and 23.

Var. 14¼° E.

5 00 Cross dry gulch 100 lks. wide, course S.; thence along north edge of table land through field of Henry Roberts.

40 00 Set post for temporary ¼ section corner.

Thence along on S. slope of rocky hill.

65 00 Summit of spur, course NW & SE. and descend.

69 50 Enter valley of San Gabriel River.

76 00 Cross San Gabriel River 50 lks. wide, course SE.

77 50 Enter field, course NW & SE.

80 14 Intersect N & S. line 16 lks. N. of corner to Secs. 13, 14, 23 and 24. From this corner I run

NORTH 89° 53' W. on true line between Sections 14 and 23.

Var. 14¼° E.

40 07 Set a Cottonwood post 3 x 3 in., 3 ft. long, in mound of rocks on side hill facing S., as instructed, for ¼ section corner.

80 14 The true corner to sections 14, 15, 22 and 23.

Land very rough, West $\frac{1}{2}$, mostly 1st. rate soil.
East $\frac{1}{2}$ very rough; scattering timber.

From the corner to Sections 22, 23, 26 and 27, I run
WEST on true line Between Sections 22 and 27.

Var. $14\frac{1}{4}^{\circ}$ E.

4 99 Int. the E. bound. of the Rancho Azusa, 21 49 chs. N. 4° W.
of corner No. 15 of said Rancho. Set an alder post 4 x 4 in.
3 ft. long in mound of rocks, as instructed, for corner to
frac. secs. 22 and 27, thence continuing West between secs.
22 and 27, thru Rancho Azusa.

8 50 Cross Sanja, course S.

40 00 Set Alder post 3 x 3 in. 3 ft. long in mound of rocks in
brushy bed of San Gabriel River, last. for $\frac{1}{4}$ section corner.

65 00 Enter wash of river, course N & S.

73 23 Int. W. bound. of Rancho Azusa, 86 09 chs. S. $46\frac{1}{2}^{\circ}$ W. of
corner No. 12 of said Rancho.
Set cedar post 4 x 4 in. 3 ft. long in large mound of rocks,
as instructed, for corner to frac. secs. 22 and 27.

78 50 San Gabriel River. No water as it runs in Janja.

79 50 Over river, course SW.

80 00 Set Oak post in mound of rocks, as instructed, for corner
to sections 21, 22, 27 and 28.

Land mostly through dry bushy land of San Gabriel River.
2nd. and 3rd rate.

December 2, 1875.

(W. H. Norway)

From the corner to Sections 21, 22, 27 and 28, I run

NORTH between Sections 21 and 22.

Var. $14\frac{1}{4}^{\circ}$ E.

15 40 Cross Zanja, course SW.

31 00 Leave river bottom and ascend.

37 00 Foot of rocky ridge; as the $\frac{1}{4}$ section corner will fall on rocky
ledge, not a suitable place to build a mound, I set at this point
a toyon post 3x3 in., 3 ft. long in mound of rocks on steep side
hill facing S. as instructed, for witness to $\frac{1}{4}$ section corner.

L. M. Rosmussen's house bears NE. about 7 00 chs. dist.

40 00 The true point for $\frac{1}{4}$ section corner on rocky ledge, course E & W.

389A 59 00 Summit of ridge and descend, course E & W.

80 00 Set Redwood post 4 x 4 in. 3 ft. long in mound of rocks, as instructed, for corner to sections 15, 16, 21 and 22.
Land, S $\frac{1}{2}$ level, mostly river bottom. N $\frac{1}{2}$ Mts. Good Bee rancho
Soil all 3rd rate.

EAST on a random line between Sections 15 and 22.

Var. $14\frac{1}{4}^{\circ}$ E.

7 50 Cross gulch with timber, S. 10° E. and ascend.
10 00 Summit of spur, course N & S. and descend.
20 00 Cross a ravine 50 lks wide, course SE. and descend.
40 00 Set temporary $\frac{1}{4}$ section corner post.
54 50 Summit of spur NW & SE. and descend.
79 90 Int. the N & S. line 21 lks. S. of corner to Sections 14, 15, 22 and 23. From this corner I run
S. $89^{\circ} 51'$ W. on a true line between sections 15 and 22.

Var. $14\frac{1}{4}^{\circ}$ E.

39 95 Set an Oak post 3 x 3 in., 3 ft. long in a large mound of rocks on SW. slope of Mts., as instructed, for $\frac{1}{4}$ section corner.

79 90 The corner to Sections 15, 16, 21 and 22.

Land rough, Mts. 3rd rate. Timber in Canadas.

Good Bee rancho

December 2, 1875.

(Norway)

From the established corner to Sections 15, 16, 21 and 22, which is a post 4 x 4 in., marked

T 1 N., Sec. 15, on NE. R 10 W., Sec. 22, on SE.

Sec 21, on SW. and Sec. 16, on NW. faces; with large mound of rocks around post.

NORTH between Sections 15 and 16, retracing 40 chains.

Var. $14^{\circ} 29'$ E.

Descending.

1A19 21 50 Gulch 50 lks. wide, course NE. Ascend.

40 00 After diligent search, being unable to find old corner, I set a sandstone 19 x 12 x 8 in., 14 in. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on West face and raised mound of stone alongside.

Pits impracticable.

50 00 Summit of ridge bears N. 50° W. and S. 50° E. Descend.

66 50 Ravine 40 lks wide, course E. Ascend.

80 00 Set granite stone 16 x 12 x 9 in., 11 in. in the ground for

corner to sections 9, 10, 15 and 16, marked with 4 notches on the South and 3 notches on the East edges and raised mound of stone alongside. Pits impracticable.

Land mountainous. Soil 3rd rate.

Timber scattering Pine and Oak in ravines.

Dense undergrowth of Chaparral.

EAST on a random line between Sections 10 and 15.

Var. 14° 29' E.

40 00 Set temporary $\frac{1}{4}$ section corner.

80 40 Intersect N & S. line 46 lks. North of corner to Secs. 10, 11, 14, and 15. Thence I run

N. 89° 40' W. on a true line between Sections 10 and 15, with same variations.

Descend.

7 50 Gulch 20 lks. wide, course S. Ascend.

17 50 Point of spur bears S. and descend.

30 00 Ravine 45 lks. wide, course SE and ascend.

40 20 Set Sandstone 16 x 11 x 5 in. 11 in. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on North face and raised mound of stone alongside. Pits impracticable.

63 50 Top of ridge bears NW & SE. Descend.

80 40 The corner to Sections 9, 10, 15 and 16.

Land mountainous. Soil 3rd rate.

Timber, Pine and Oak in ravines.

Dense undergrowth of Chaparral.
