

FIELD NOTES

Township 2 N., Range 8 W.,

S. B. M.

North Line Sec. 30

North Line Sec. 29

North Line Sec. 28

North Line Sec. 27

North Line Sec. 26

West Line Sec. 17

North Line Sec. 17

West Line Sec. 8

West Line Sec. 5

-----

<b>R. 8 W.</b>						
	6	<sup>1</sup> 5	4			
	7	<sup>9</sup> <sub>8</sub> 8	9			
	18	<sup>8</sup> 7 17	7 16			<b>T. 2 N.</b>
<b>24</b>	19	<sup>6</sup> 20	21	22	23	24
<b>25</b>	<sup>5</sup> 30	<sup>6</sup> <sub>4</sub> 29	<sup>4</sup> <sub>3</sub> 28	<sup>3</sup> <sub>3</sub> 27	<sup>2</sup> <sub>2</sub> 26	<sup>1</sup> <sub>1</sub> 25
<b>36</b>	31	32	33	34	35	36

T. 2 N., R. 8 W., S. B. M.

North between sections 25 and 30.

Var.  $14^{\circ} 12\frac{1}{2}'$  East.

80.00 Set sand stone 20 x 11 x 9 in., 15 in. in the ground for corner to sections 19, 24, 25 and 30.

Marked with 4 notches on the North and 2 notches on the South edges and raised a mound of stone alongside.

Pits impracticable.

Land mountainous. Soil second rate.

Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

-----

North  $80^{\circ} 40'$  West on a true line between sections 5 and 32.

Var.  $14^{\circ} 12\frac{1}{2}'$  East.

80.00 Set sand stone 13 x 11 x 10 ins., 8 in. in the ground for corner to sections 5, 6, 31 and 32.

Marked with 5 notches on the East and 1 notch on the West edges and raised a mound of stone alongside.

Pits impracticable.

Land mountainous. Soil third rate.

Timber none. Dense undergrowth of Chaparral.

-----

North between sections 25 and 36. <sup>26</sup>

Var.  $14^{\circ} 26\frac{1}{2}'$  East.

80.00 Set granite stone 15 x 11 x 9 in., 10 in. in the ground for corner to sections 23, 24, 25 and 26.

Marked with 1 notch on the East and 1 notch on the South edges and raised a mound of stone alongside.

Pits impracticable.

Land mountainous. Soil third rate.

No timber. Dense undergrowth of Chaparral.

-----

North between sections 26 and 27.

Var.  $14^{\circ} 26\frac{1}{2}'$  East.

80.00 Set sand stone 14 x 9 x 8 in., 9 in. in the ground  
for corner to sections 22, 23, 26 and 27.  
Marked with 2 notches on South and East edges and  
raised mound of stone alongside.

Pits impracticable.

From which bears an

Oak 14 in. dia. S. 23 3/4° W., 1.67 chs. dist.  
T. 2 N., R. 8 W., S. 27 B. T.

Pine 8 in. dia. N. 7° E., 2.61 chs. dist. marked  
T. 2 N., R. 8 W., S. 23 B. T.

No other trees within limits.

Land mountainous. Soil second rate.

Timber scattering Pine and Oak. Dense undergrowth of  
Chaparral.

-----  
East on a random line between sections 23 and 26.

Var. 14° 26 1/2' East.

40.00 Set temporary 1/4 section corner.

80.38 Intersect North and South line <sup>21</sup> links South of corner  
to sections 23, 24, 25 and 26.

Thence I run

South 89° 51' West on a true line between sections 23 and  
26 with same variations. Ascending.

17.50 Summit of divide bears Northeast and Southwest and descend.

40.19 Set sand stone 10 x 11 x 9 ins., 6 in. in the ground for 1/4  
section corner.

Marked 1/4 on North face and raised mound of stone alongside.

Pits impracticable.

51.60 Cross gulch near head, course Northwest and ascend.

80.38 The corner to sections 22, 23, 26 and 27.

-----  
North between sections 27 and 28.

Var. 14° 26½' East.

80.00 Set granite stone 21 x 14 x 6 in., 6 in. in the ground  
for corner to sections 21, 22, 27 and 28.

Marked with 2 notches on the South and 3 notches on the  
East edges and raised a mound of stone alongside.

Pits impracticable.

Land mountainous. Soil third rate.

Timber scattering Pine and Oak. Dense undergrowth of  
chaparral.

-----  
East on a random line between Sections 22 and 27  
Var. 14° 26½' East.

40.00 Set temporary ¼ section corner.

80.43 Intersect North and South line 19 links North of corner  
to sections 22, 23, 26 and 27.

Thence I run

North 89° 52' West on a true line between sections 22 and  
27 same variation. Ascend.

39.60 Summit of spur bears North 50° West and descend.

40.22 Set sand stone 12 x 11 x 7 in., 7 in. in the ground for  
¼ section corner.

Marked ¼ on North face and raised mound of stone alongside.

Pits impracticable.

77.60 Gulch 30 links wide, course Northwest and ascend.

80.43 The corner to sections 21, 22, 27 and 28.

Land mountainous. Soil third rate.

Timber scattering Pine and Oak. Dense undergrowth of chaparral.

-----  
North between sections 28 and 29.

Var. 14° 26½' East.

80.00 Set granite stone 19 x 11 x 15 in., 14 in. in the ground  
for corner to sections 20, 21, 28 and 29.

Marked with 4 notches East and 2 notches on the South  
edges and raised mount of stone alongside.

Pits impracticable.

Land mountainous. Soil third rate.

Timber Pine and Oak in ravine. Dense undergrowth of chaparral.

-----

East on a random line between sections 21 and 28.

Var.  $14^{\circ} 26\frac{1}{2}'$  East.

40.00 Set temporary  $\frac{1}{4}$  section corner.

80.00 Intersect East and South line at corner to sections 21, 22,  
27 and 28.

Thence I run

West on a true line between sections 21 and 28 with same variation.

Descend gradually and along South bank of creek in Cow Canon.

40.00 Set granite stone 13 x 12 x 7 in., 8 in. in the ground Marked  
on North face,

From which bears a

Sycamore 14 in. dia. North  $20^{\circ}$  W., 17 lks. dist.  
Pine 16 in. dia. South  $39^{\circ}$  E. 1.17 chs. dist.

Both marked  $\frac{1}{4}$  S. B. T.

72.00 Leave Canon and ascend North slope of spur.

80.00 The corner to sections 20, 21, 28 and 29.

Land mountainous. Soil second rate.

Timber Pine, Oak and Sycamore in the Canon.

Dense undergrowth of Chaparral.

-----

North between sections 29 and 30.

Var.  $14^{\circ} 26\frac{1}{2}'$  East.

80.00 Set granite stone 12 x 11 x 8 in., 7 in. in the ground for  
corner to sections 19, 20, 29 and 30.

Marked with 2 notches on the South and 5 notches on

East edges.

From which bears a

Pine 22 in. dia. N. 71° E., 1.09 chs. dist. marked  
T. 2 N., R. 8 W., Section 20, B. T.

Pine 18 in. dia. N. 47° W., 94 lks. dist. marked  
T. 2 N., R. 8 W., Section 19 B. T.

Pine 10 in. dia. S. 81° W., 78 lks. dist. marked  
T. 2 N., R. 8 W., Section 30 B. T.

Pine 14 in. dia. S. 14° E., 66 lks. dist. marked  
T. 2 N., R. 8 W., Section 29 B. T.

Land mountainous. Soil third rate.

Timber Pine and Oak in Canon. Dense undergrowth of chaparral.

-----  
West on a random line between sections 19 and 30.

Var. 14° 26½' East.

40.00 Set temporary ¼ section corner.

82.88 Intersect West boundary of Tp. 47 lks. North of corner  
to sections 19, 24, 25 and 30.

Thence I run

North 89° 40' East on a true line between sections 19 and  
30 with same variations. Descend.

21.00 Enter San Gabriel Canon, course South 10° West.

21.70 San Gabriel River 60 lks. wide, course South 10° W.

28.60 Leave canon, course South 10° West, and ascend.

42.88 Set granite stone 17 x 9 x 8 in., 12 in. in the ground for  
¼ section corner marked ¼ on North face and raised mound of  
stone alongside.

Pits impracticable.

47.60 Point of spur bears Southwest and descend.

82.88 The corner to sections 19, 20, 29 and 30.

Land mountainous. Soil third rate.

Timber Pine and Oak in ravine. Dense undergrowth of  
Chaparral Brush.

East on a random line between sections 20 and 29.

Var.  $14^{\circ} 26\frac{1}{2}'$  East.

40.00 Set temporary  $\frac{1}{4}$  section corner.

80.18 Intersect North and South line 41 lks. South of corner to sections 20, 21, 28 and 29.

Thence I run

South  $89^{\circ} 42'$  West on a true line between sections 20 and 29 with same variation. Ascend.

22.60 Point of spur bears Northwest and descend.

40.09 Set granite stone 13 x 11 x 7 in., 8 in. in the ground for  $\frac{1}{4}$  section corner marked  $\frac{1}{4}$  on North face.

From which bears an

Oak 14 in. dia. S.  $19^{\circ}$  E., 42 lks.  
Pine 18 in. dia. S.  $22^{\circ}$  W., 93 lks.  
Both marked  $\frac{1}{4}$  S. B. T.

40.60 Enter Cow Canon, course South.

47.00 Creek 12 lks. wide, course South.

48.15 Leave Canon, course South and ascend.

80.18 The corner to sections 19, 20, 29 and 30.

Land mountainous. Soil 2nd rate.

Timber Pine and Oak in Canon. Dense undergrowth of chaparral.

-----

North between sections 19 and 20.

Var.  $14^{\circ} 26\frac{1}{2}'$  East.

80.00 Set sand stone 17 x 12 x 6 in., 12 in. in the ground for corner to sections 17 and 18, 19 and 20.

Marked with 3 notches on South and 5 notches on the E. edges.

From which bears a

Pine 14 in. dia. N.  $11^{\circ}$  E., 49 lks. marked  
T. 2 N., R. 8 W., Section 17 B. T.

Pine 18 in. dia. N.  $17\frac{1}{2}^{\circ}$  W., 119 chs. marked  
T. 2 N., R. 8 W., Section 18 B. T.

Oak 20 in. dia. S.  $60^{\circ}$  W., 1.33 chs. marked  
T. 2 N., R. 8 W., Section 19 B. T.

Pine 20 in. dia. South 48° E. 1.46 chs. marked  
T. 2 N., R. 8 W., Section 20 B. T.

Land Mountainous. Soil second rate.

Timber Pine and Oak in canon. Dense undergrowth of chaparral.

-----  
North between sections 16 and 17. Var. 14° 26½' East.

80.00 Set granite stone 19 x 12 x 8 in., 14 in. in the ground for  
corner to sections 8, 9, 16 and 17.

Marked with 4 notches on South and 4 notches on the East  
edges and raised mound of stone alongside.

Pits impracticable.

Land mountainous. Soil third rate.

Timber none. Dense undergrowth of chaparral.

-----  
North between sections 17 and 18. Var. 14° 26½' East.

Ascend on low point.

11.00 Leave point and descend abruptly into San Gabriel Canon.

19.00 Cross San Gabriel River 45 lks. wide, course S. 30° East.  
Thence up Canon.

30.00 San Gabriel River 50 lks. wide, course South 40° West.

36.00 Leave Canon, course South 40° West and ascend.

40.00 Set sand stone 14 x 12 x 6 in., 9 in. in the ground for ¼  
section corner, marked ¼ on West face,

From which bears a

Pine 14 in. dia. N. 80° East, 2.10 chs. dist.  
Oak 18 in. dia. N. 46° W. 1.55 chs. dist.

Both marked ¼ S. B. T.

56.50 Point of spur bears S. 10° E. and descend.

80.00 Set sand stone 15 x 11 x 7 in., 10 in. in the ground for

corner to sections 7, 8, 17 and 18.

Marked with 4 notches on South and 5 notches on East  
edges and raised mound of stone alongside.

Pits impracticable.

Land mountainous. Soil third rate.

Timber Pine and Oak in Canon. Dense undergrowth of chaparral.

-----  
East on a random line between sections 8 and 17.

Var.  $14^{\circ} 26\frac{1}{2}'$  East.

40.00 Set temporary  $\frac{1}{4}$  section corner.

80.10 Intersect North and South line 21 links South of corner, to  
sections 8, 9, 16 and 17.

Thence I run

South  $89^{\circ} 51'$  West on a true line between sections 8 and 17,  
with same variation. Ascend.

17.30 Top of spur bears Southwest and descend.

40.05 Set granite stone 13 x 8 x 7 in., 8 in. in the ground for  $\frac{1}{4}$   
section corner.

Marked  $\frac{1}{4}$  on North face and raised mound of stone alongside.

Pits impracticable.

56.40 Enter San Gabriel Canon, course South  $3^{\circ}$  East.

58.70 San Gabriel River 45 lks. wide, course  $3^{\circ}$  East.

61.50 Leave Canon, course Southeast and ascend.

80.10 The corner to sections 7, 8, 17 and 18.

Land mountainous. Soil second rate.

Timber Pine and Oak in Canon. Dense undergrowth of chaparral.

-----  
North between sections 7 and 8.

Var.  $14^{\circ} 26\frac{1}{2}'$  East.

Descend.

- 21.70 Enter San Gabriel Canon, course South 15° East.
- 31.40 San Gabriel River 50 lks. wide, course South 15° East.
- 40.00 Set sand stone 12 x 9 x 8 in., 7 in. in the ground for  $\frac{1}{4}$  section corner, marked  $\frac{1}{4}$  West face, raised mound of stone alongside.
- 40.80 San Gabriel River 50 links wide, course South 20° West.
- 51.00 Leave canon, course South 15° West, and ascend spur.
- 80.00 Set granite stone 13 x 11 x 10 in., 8 in. in the ground for corner to sections 5, 6, 7 and 8.  
Marked with 5 notches on the South and East edges and raised mound of stone alongside.  
Pits impracticable.  
Land mountainous. Soil third rate.  
Timber Pine and Oak in Canon. Dense undergrowth of chaparral.
- 
- North on a random line between sections 5 and 6.  
Var. 14° 26 $\frac{1}{2}$ ' East.
- 40.00 Set temporary  $\frac{1}{4}$  section corner.
- 83.97 Intersect North boundary of T. 1.73 lks. West of corner to sections 5, 6, 31 and 32.  
Thence I run  
South 0° 31' West on a true line between sections 5 and 6 with same variation. Ascending.
- 43.97 Set granite stone 18 x 11 x 7 in., 13 in. in the ground for  $\frac{1}{4}$  section corner marked  $\frac{1}{4}$  on West face and raised mound of stone alongside.  
Pits impracticable.
- 69.00 Top of spur bears South 5° West and descend.
- 83.97 The corner to section 5, 6, 7 and 8.  
Land mountainous. Soil third rate.  
Timber scattering Pine and Oak. Dense undergrowth of chaparral.
-