

RETURN TO  
 COUNTY SURVEYOR,  
 LOS ANGELES.

F I E L D N O T E S .

Township 3 N.      Range 11 W.

S. B. M.

East Line Sec. 36

East Line Sec. 25

South Line Sec. 25

North Line sec. 25.

W. Line <sup>0</sup> Secs. 25, 36.

	R. 11 W.						
	6	5	4	3	2	1	
	7	8	9	10	11	12	
T. 3 N.	18	17	16	15	14	13	T. 3 N.
	19	20	21	22	23	24	
	30	29	28	27	26	<sup>4</sup> 25	
	31	32	33	34	35	<sup>2</sup> 36	
	R. 11 W.						

Sixth Mile East.

East on the true line on North Boundary of section 1.

Var.  $14\frac{1}{2}^{\circ}$  East.

80.00

Set a Pine post 6 x 6 in., 4 ft. long, in a large mound on steep side of low brush hill, as instructed, for corner to Tps. 2 and 3 N., Rs. 10 and 11 W. on S. B. Meridian and Base.

Land along this line third rate. Soil second rate, good Pine in Canadas, scattering Pine on mountain.

-----o-----

From the corner to Tps. 2 and 3 N., Rs. 10 and 11 W.,

I run

North between Rs. 10 and 11,

North on the East boundary of section 36.

Var.  $14\frac{1}{2}^{\circ}$  East.

18.00

Cross gulch in a deep timbered Canadas,

"A branch of the San Gabriel River," course Southeast and ascend.

33.00

Summit of spur, bearing North and Southeast, descend.

40.00

Set a Pine post 3 x 3 in., and 3 ft. long in a mound of rocks as instructed on side hill, facing Northeast for  $\frac{1}{2}$  section corner, from which bears a

Norway Pine 34 in. dia., N.  $76^{\circ}$  W., 18 lks. dist.

60.50

Cross gulch 50 lks. wide, course Southwest. Ascend.

80.00

Set a rock 6 x 10 x 24 in. in a mound of rocks as instructed, for corner to sections 25, 30, 31 and 36.

Land very rough, second rate, Pine in Canadas.

-----o-----

North on East boundary of section 25.

Var.  $14\frac{1}{2}^{\circ}$  East.

20.00

Summit of spur bearing Northeast and Southwest. Descend

40.00

The point for  $\frac{1}{2}$  section corner falling in deep gulch

Course Southwest, not a suitable place to build a mound

I continue at,

42.50 Set a Pine post 3 x 3 in., 3 ft. long in a mound of rocks, as instructed, for witness to  $\frac{1}{4}$  section corner and ascend.

61.50 Summit of spur bearing Northeast and Southwest. Descend.

80.00 Set a Redwood post 4 x 4 in., 3 $\frac{1}{2}$  ft. long in a mound of rock, as instructed, for corner to sections 19, 24, 25 and 30,

From which bears a  
Norway Pine 3 ft. dia. N. 1° W., 20 lks. dist.  
Pitch Pine 24 in. dia. S. 23° E., 70 lks. dist.  
Land rough, mostly first rate Pine.

-----o-----

From the corner to sections 35 and 36 on Southern boundary of Tp. I run  
North between sections 35 and 36.  
Var. 14 $\frac{1}{2}$ ° East.

Descending.

80.00 Set a Pine post 4 x 4 in., 3 $\frac{1}{2}$  ft. long in a mound of rocks, as instructed, for corner to sections 25 and 26, 35 and 36.  
Land very rough. Good Pine and Fir timber in Canadas.  
Soil third rate.

-----o-----

East on a random line between sections 25 and 36.  
Var. 14 $\frac{1}{2}$ ° East.

40.00 Set post for temporary  $\frac{1}{4}$  section corner.

80.00 Cross branch of San Gabriel 1.50 chs. wide, course South. No water and ascending.

79.84 Intersect the Eastern Boundary of Tp. 12 lks. South of the corner to sections 25 and 36, from this corner I run  
South 89° 55' W. on a true line between sections 25 and 36.

39.92

Var.  $14\frac{1}{2}^{\circ}$  East.

The point for  $\frac{1}{4}$  section corner falling in deep gulch, not a suitable place to build a mound, I set a Pine post 3 x 3 in., 3 ft. long in a mound of rocks 150 lks. W., as instructed, for witness to  $\frac{1}{4}$  section corner,

From which bears a

Pitch Pine 12 in. dia. N.  $36^{\circ}$  W., 24 lks. dist.

79.84

The corner to sections 25 and 26, 25 and 26.

Land very rough. Timber scattering, second rate Pine and Fir.

-----O-----

North between sections 25 and 26.

Var.  $14\frac{1}{2}^{\circ}$  East.

The land between these sections extends up and abrupt broken side hill, too rough to measure and to obtain distance I cause a flag to be sent North on summit of the high spur and in the line between sections 25 and 26 run a base East of 5.00 chs. to the point, where my flag bears N.  $50^{\circ} 10'$  W., which would give, by calculation, a distance of 55.29 chs. of my flag, being unable to return and set a  $\frac{1}{4}$  section corner I set a Redwood post 3 x 3 in., 3 ft. long in a mound of rocks in place of the flag on top of the high spur, as instructed for witness to  $\frac{1}{4}$  section corner.

80.00

set a Pine<sup>post</sup>  $\frac{1}{4}$  x 4 in.,  $5\frac{1}{2}$  ft. long in a mound of rocks, as instructed, for corner to sections 23, 24, 25 and 26,

From which bears a

Yellow Pine 3 ft. dia. N.  $17^{\circ}$  W., 38 lks. dist.

Pitch Pine 12 ft. dia. S.  $21^{\circ}$  E., 45 lks. dist.

Land very rough. First rate scattering Pine in places.

-----O-----

East on a random line between sections 24 and 25.

Var.  $14\frac{1}{2}^{\circ}$  East.

1.50	Cross gulch 50 lks. wide, course Southeast.
20.00	Cross dry gulch 50 lks. wide, course Southeast. Thence Along South slope to hill.
40.00	Set post for temporary $\frac{1}{2}$ section corner.
65.00	Enter Canadas at foot of hill, course Northwest and Southeast.
67.50	Cross dry branch of San Gabriel, at junction of two gulchs 150 lks. wide, course Southwest.
80.00	Intersect the Eastern boundary of the Tp. 21 lks. North of the corner to sections 24 and 25,  From this corner I run North $89^{\circ} 51'$ West on a true line between sections 24 and 25.  Var. $14\frac{1}{2}^{\circ}$ East.
40.00	Set a Pine post 3 x 3 ft., 3 ft. long in a large mound of rocks, as instructed, on steep side of hill, facing South for $\frac{1}{2}$ section corner.
80.00	The corner to sections 23, 24, 25 and 26. Land very rough. First rate Pine in Canadas.

-----o-----