

U. S. Field Notes of Survey  
of  
Certain Section Lines in T. 6 N.,  
R. 17 W. S.B.M.  
California

Section Lines between

Sections 35 & 36  
25 & 36  
25 & 26  
23 & 24  
13 & 14  
11 & 12  
26 & 27  
23 & 26  
22 & 23  
14 & 23  
14 & 15  
11 & 14  
10 & 11  
2 & 11  
2 & 3  
27 & 28  
22 & 27  
21 & 22  
15 & 16  
10 & 15  
9 & 10  
3 & 10  
15 & 22

R.17W.							
T.6N.	6	5	4	3	2	1	T.6N.
				<sup>12</sup>	<sup>8</sup>		
	7	8	9	<sup>12</sup> 10	7	11	12
				<sup>11</sup>	<sup>7</sup>		
	18	17	16	<sup>11</sup> 15	7	14	13
				<sup>10</sup>	<sup>6</sup>		
	19	20	21	<sup>10</sup> 22	5	23	24
				<sup>9</sup>	<sup>4</sup>		
	30	29	28	<sup>9</sup> 27	4	26	25
				<sup>9</sup>	<sup>4</sup>		
	31	32	33	34	35	36	
	R.17W.						

Norway 1879

(Surveyed by W. S. Norway,  
Contract of Oct. 10, 1897,  
Book, 164, Part 16.)

T. 6 N., R. 17 W., S.B.W.,  
From the corner to sections 35, 36, ~~X & X~~, on the south  
boundary, I run  
2 & 3

North, between sections 35 and 36.

Variation 14°25' East

Ascend.

- 7.50 Summit of high ridge, bears NW and SE and descend.  
15.00 Cross low sag and ascend.  
40.00 Set post 4 in. dia., 1 ft. in earth, 1 ft. above earth  
mound, 4 ft. in diameter at base by 2 ft. in height and dug  
pit 24x18x12, 8 lks. east for  $\frac{1}{4}$  sec. cor.  
80.00 To a point on steep side hill, not a suitable place to  
build mound, I leave a flag from which a flag left at  
corner to sections 25 and 36, bears due east.  
Land mountainous. Soil 1st rate.  
Timber and undergrowth of oak and chaparral.  
Barron's house near center of sec. 36.

---

East on a random line between secs. 25 and 36.

Variation 14°25' E.

Descend.

- 9.50 Enter valley of Canada Castaque, bears NW and SE  
10.00 Cross creek 25 lks. wide, course SE.  
17.75 Cross road, bears NW and SE  
40.00 Set temporary  $\frac{1}{4}$  sec. cor.  
40.50 Cross gulch 20 lks. wide, course SW.  
46.50 Leave valley Castaque, bears NW and SE and ascend.  
80.15 Intersect east boundary of Tp. at corner to sections 25

and 36, from which corner, I run west on a true line between sections 25 and 36.

Var.  $14^{\circ}25'$  E.

- 40.09 Set post 4 in. dia., 1 ft. in earth, 1 ft. above stone mound, 4 ft. in diameter at base, by 2 ft. in height for  $\frac{1}{4}$  sec. cor., from which Barron's house, bears south, about 35.00 chs. dist.
- 70.50 Set post 4 ins. square 1 ft. in earth, 1 ft. above stone mound, 4<sup>o</sup> ft. in dia. at base, by 2 ft. in height for witness to cor. to secs. 25, 26, 35, 36.
- 80.18 The corner to sections 25, 26, 35, 36.  
Land mountainous, except in valley.  
Soil 1st and 2nd rate.  
Timber and undergrowth of oak and chaparral.

---

North between sections 25 and 26

Var.  $14^{\circ}25'$  East

Descend.

- 5.00 Enter Canada Castaque, bears NW and SE and set post 4 in. square, 1 ft. in earth, 1 ft. above stone mound  $4\frac{1}{2}$  ft. in dia. at base, by 2 ft. in height, for witness to corn. to secs. 25, 26, 35, 36, from which bears a Sycamore 14 in. dia. N.  $61\frac{1}{2}^{\circ}$  W. 194 lks. dist.
- 6.00 Cross Castaque Creek, 50 lks. wide, course S.E.
- 13.00 Cross road, bears NW and SE
- 36.50 Leave canada bears NE and SW and ascend.
- 40.00 Set stone 20x18x12 in stone mound, 4 ft. in diameter at base by 2 ft. in height for  $\frac{1}{4}$  sec. cor.  
Burett's house, bears NW about 15.00 chs. dist.
- 57.50 Summit of spur, bears NE and SW and descend.
- 80.00 Set stone 20x16x10 in stone mound,  $4\frac{1}{2}$  ft. in diameter at base by 2 ft. in height for corner to sections 23, 24, 25, 26.

Land mountainous, except in valley. Soil 1st and 2nd rate.  
Timber and undergrowth of oak, cedar, sycamore and chaparral.

---

North between sections 23 and 24.

Var.  $14^{\circ}25'$  E.

80.00 Set post, 4 in. square, 1 ft. in earth, 1 ft. above stone mound, 4<sup>o</sup> ft. in diameter at base, by 2 ft. in height, for corner to sections 13, 14, 23, 24.

Land mountainous. Soil 2nd rate. Timber and undergrowth of oak and chaparral.

April 26th, 1880.

North between sections 13 and 14.

Var.  $14^{\circ}25'$  E.

80.00 Set stone 16x12x10, in stone mound  $4\frac{1}{2}$  ft. in diameter at base by 2 ft. in height for corner to sections 11, 12, 13, 14.

Land mountainous. Soil 1st and 2nd rate.

Timber and undergrowth of oak, sycamore, poplar, willow and chaparral.

---

North between sections 11 and 12.

Var.  $14^{\circ}25'$  E.

Ascend.

40.00 Set stone 16x14x10 in stone mound 4 ft. in diameter at base by 2 ft. in height for  $\frac{1}{4}$  sec. cor.

The land in advance consisting of rough and broken mountains, devoid of valuable timber with soil unfit for cultivation, I discontinue the line.

Land mountainous. Soil 2nd rate.

Timber and undergrowth of oak and chaparral.

---

North between 26 and 27.

Var.  $14^{\circ}25'$  E.

80.00 The point for section corner falling in center of ravine, not a suitable place to build mound, I run east 50 lks. and set post 4 in. square 1 ft. in earth 1 ft. above stone mound,  $4\frac{1}{2}$  ft. in diameter at base, by 2 ft. in height for witness to corner to sections 22, 23, 26 and 27.

Land mountainous. Soil 2nd rate.

Timber and undergrowth of oak and chaparral.

---

East on a random line between sections 23 and 26.

Var.  $14^{\circ}25'$  E.

.50 Witness post.

3.00 Enter valley of Castaque bears NW and SE

17.50 House bears south about 100 Yks. dist.

19.75 Cross Castaque Creek 50 lks. wide, runs SE

21.00 Cross road, bears NW and SE

34.00 Leave valley Castaque, bears NW and SE and ascend.

40.00 Set temporary  $\frac{1}{4}$  sec. cor. and descend.

71.50 Cross gulch 18 lks. wide, course SW and ascend.

79.96 Intersect N & S line 12 lks. north of corner to sections 23, 24, 25, 26, from which corner I run N.  $89^{\circ}55'$  W. on a true line between sections 23 and 26.

Var.  $14^{\circ}25'$  E.

39.98 The point for  $\frac{1}{4}$  sec. corn. falling on steep side hill, a place not suitable to build mound, I run west 4.57 chs. and set post 4 in. dia. 1 ft. in earth, 1 ft. above stone mound, 4 ft. in dia. at base, by 2 ft. in height for

witness to  $\frac{1}{4}$  sec. cor.

79.96 The corner to sections 22, 23, 26, 27.

Land mountainous, except in valley. Soil 1st and 2nd rate.  
Timber and undergrowth of oak, cedar, poplar, willow and  
chaparral.

---

North between sections 22 and 23.

Var.  $14^{\circ}25'$  E.

Descend.

- .50 A gulch bears NE and SW
- 1.50 Enter valley Castaque bears NW and SE
- 9.50 Cross creek, 50 lks. wide, course SE
- 13.50 Cross trail, bears NW and SE
- 36.50 Leave valley, bears NW and SE and ascend.
- 40.00 Set post 4 in. dia. 1 ft. in earth, 1 ft. above stone  
mound, 4 ft. in dia. at base, by 2 ft. in height for  
 $\frac{1}{4}$  sec. cor. from which one of a cluster of sycamores  
12 in. dia., bears West 11.98 chs. dist.
- 62.50 Summit of spur, bears E. & W. & descend.
- 80.00 The point for section corner falling on steep side hill,  
a place not suitable to build mound, I run west 1.97 chs.  
and set post 4 in. square, 1 ft. in earth, 1 ft. above  
stone mound,  $4\frac{1}{2}$  ft. in dia. at base, by 2 ft. in height,  
for witness to corner to secs. 14, 15, 22, 23, from which  
bears a  
Sycamore 24 in. dia. N.  $80\frac{1}{2}^{\circ}$  W. 137 lks. dist.  
Land mountainous, except in valley.  
Soil 1st and 2nd rate.  
Timber and undergrowth of oak, cedar, sycamore, willow and  
chaparral.

East on a random line between sections 14 and 23.

Var.  $14^{\circ}25'$  E.

Ascend.

- 40.00 Set temporary  $\frac{1}{4}$  sec. cor.
- 43.00 Summit of spur bears NE and SW. and descend.
- 80.24 Intersect N & S line 22 lks. north of corner to sections 13, 14, 23, 24, from which corner I run N.  $89^{\circ}51'$  W. on a true line between sections 14 and 23.
- Var.  $14^{\circ}25'$  E.
- 40.12 Set post 4 in. dia. 1 ft. in earth. 1 ft. above stone mound, 4 ft. in dia. at base, by 2 ft. in height, for  $\frac{1}{4}$  sec. cor.
- 80.24 The corner to sections 14, 15, 22, 23.  
Land mountainous. Soil 2nd rate.  
Timber and undergrowth of oak and chaparral.

---

North between sections 14 and 15.

Var.  $14^{\circ}25'$  E.

From true corner.

- 1.50 Enter Canada, bears NE and SW
- 2.25 Cross creek, 50 lks. wide, course SW
- 4.50 Leave Canada bears NE and SW and ascend.
- 19.50 Summit of spur, bears NE and SW and descend.
- 26.40 Cross head of gulch, 50 lks. wide, course NW and ascend.
- 33.00 Summit of spur, bears E. & W. and descend.
- 40.00 The point for  $\frac{1}{4}$  sec. cor. falling on steep side hill not suitable place to mark corner, I continue and at
- 52.66 To foot of mountain in Canada Castaque, bearing NE and SW to sycamore tree 10 in. dia. which I mark for witness to  $\frac{1}{4}$  sec. cor.
- 53.00 Cross Castaque Creek, 30 lks. wide, runs SW
- 54.50 Leave Canada, bears NE and SW and ascend.

80.00 Set post 4 in. square, 1 ft. in earth, 1 ft. above stone mound,  $4\frac{1}{2}$  ft. in dia. at base, by 2 ft. in height, for cor. to secs. 10, 11, 14, 15, from which bears a Sycamore 14 in dia. N.  $82\frac{1}{2}^{\circ}$  E. 60 lks. dist.  
Land mountainous, except in valley.  
Soil 2nd rate.  
Timber and undergrowth of oak, cottonwood, sycamore & chaparral.

---

East on a random line between sections 11 and 14.

Var.  $14^{\circ}25'$  E.

Descend.

1.25 Cross Castaque Creek, 30 lks. wide, course SE  
2.00 A canada, bears NW and SE and ascend.  
40.00 Set temporary  $\frac{1}{4}$  sec. cor.  
47.50 Summit of spur, bears NE and SW and descend.  
80.32 Intersect N and S. line 12 lks. south of corner to sections 11, 12, 13, 14, from which corner, I run S.  $89^{\circ}55'$  W. on a true line between sections 11 and 14.

Var.  $14^{\circ}25'$  E.

40.16 Set stone 16x14x10 in stone mound, 4 ft. in diameter at base by 2 ft. in height for  $\frac{1}{4}$  sec. cor.  
80.32 The corner to sections 10, 11, 14, 15.  
Land mountainous. Soil 2nd rate. Timber and undergrowth of oak, sycamore, cottonwood, willow and chaparral.

April 28, 1880

---

North between sections 10 and 11.

Var.  $14^{\circ}25'$  E.

Along west edge of Canada Castaque.

3.00 Enter same and cross creek 30 lks. wide, course SE

- 7.50 Leave Canada and ascend along east side of same over point of mountain and descend.
- 22.00 Enter canada, thence up same.
- 26.00 Cross creek, 130 lks. wide, course SW
- 33.00 Leave canada and ascend.
- 40.00 The point for  $\frac{1}{4}$  sec. cor. falling on steep side hill, not a suitable place to build mound, I continue north 1.55 chs. and set post, 4 in. dia., 1 ft. in earth, 1 ft. above stone mound, 4 ft. in diameter at base, by 2 ft. in height for witness to  $\frac{1}{4}$  sec. cor. from which bears a cottonwood, 14 in. dia. N. 38° W. 58 lks. dist. Cottonwood 14 in. dia. S. 80° E. 88 lks. dist. Thence descending.
- 43.25 Cross Castaque Creek, 30 lks. wide, runs S. E.
- 45.00 A canada, bears NW and SE and ascend.
- 80.00 Set stone 16x12x6 in. stone mound, 4 $\frac{1}{2}$  ft. in dia. at base, by 2 ft. in height, for corner to sections 2, 3, 10, 11 Land mountainous, except in canadas. Soil 1st and 2nd rate. Timber and undergrowth of oak, cedar, cottonwood, sycamore and chaparral.

---

East on a true line between sections 2 and 11

Var. 14°25' E.

- 5.00 Descend.
- 20.00 Enter canada, bears NE and SW
- 22.00 Cross gulch, 20 lks. wide, course SW
- 30.00 Leave canada, and ascend.
- 40.00 Finding the land in advance too rough and worthless to continue further on this line, I set stone 12x10x6 in stone mound, 4 ft. in dia. at base, by 2 ft. in heights, for  $\frac{1}{4}$  sec. cor. and return to corner to secs. 2, 3, 10, 11. Land mountainous. Soil 2nd rate. Timber and undergrowth of oak and chaparral.

North on a random line between secs. 2 and 3.

Var.  $14^{\circ}25'$  E.

Ascend.

40.00 Set temporary  $\frac{1}{4}$  sec. cor.

60.00 Summit of spur, bears NE and SW and descend.

80.30 Intersect north boundary of Tp. 34 lks. east of corner to sections 2 and 3, from which corner, I run S.  $15^{\circ}$  E. on a true line between sections 2 and 3.

Var.  $14^{\circ}25'$  E.

40.30 Set stone  $14 \times 10 \times 6$  in stone mound, 4 ft. in diameter at base, by 2 ft. in height, for  $\frac{1}{4}$  sec. cor.

80.30 The corner to sections 2, 3, 10, 11.

Land mountainous. Soil 2nd rate.

Timber and undergrowth of oak and chaparral.

---

North between sections 27 and 28.

Var.  $14^{\circ}25'$  E.

80.00 The point for section corner falling in deep wash a place not suitable to build mound, I run west 15.00 chs. and set post 4 in. square, 1 ft. in earth, 1 ft. above stone mound,  $4\frac{1}{2}$  ft. in dia. at base, by 2 ft. in height, for witness to corner to sections 21, 22, 27, 28.

Land mountainous. Soil 2nd rate.

Timber and undergrowth of oak and chemical.

---

East on a random line between sections 22 and 27.

Var.  $14^{\circ}25'$  E.

Descend.

4.00 A wash bears NE and ascend.

21.50 Summit of spur, bears NE and SW and cross trail to Castaque Canada.

- 22.50 Descend.
- 40.00 Set temporary  $\frac{1}{4}$  sec. cor.
- 45.00 Enter canada, bears NE and SW.
- 50.00 Cross gulch, 30 lks. wide, course NE and leave canada and ascend.
- 61.50 Summit of spur, bears N and S and descend.
- 79.75 A gulch, bears NE and ascend.
- 80.22 Intersect N and S line 10 lks. north of corner to sections 22, 23, 26, 27, from which corner I run N.  $89^{\circ}56'$  W., on a true line between sections 22 and 27.

Var.  $14^{\circ}25'$  E.

- 40.11 Set post 4 in. dia., 1 ft. in earth, 1 ft. above earth mound, 4 ft. in dia. at base, by 2 ft. in height and dug pit,  $24 \times 18 \times 12$ , 8 lks. north, for  $\frac{1}{4}$  sec. cor.

- 80.22 The corner to sections 21, 22, 27, 28.

Land mountainous. Soil 2nd rate.

Timber and undergrowth of oak and chaparral.

April 29, 1880.

---

North between sections 21 and 22.

Var.  $14^{\circ}25'$  E.

- 80.00 Set post, 4 in. square, 1 ft. in earth, 1 ft. above earth mound  $4\frac{1}{2}$  ft. in dia. at base, by 2 ft. in height and dug pits  $24 \times 18 \times 12$ , 8 lks. dist. at 4 angles for corner to sections 15, 16, 21, 22.

Land mountainous. Soil 2nd rate.

Timber and undergrowth of oak and chaparral.

---

East on a random line between sections 15 and 22.

Var.  $14^{\circ}25'$  E.

Descend.

- 40.00 Set temporary  $\frac{1}{4}$  sec. cor.
- 56.00 Enter Canada and cross trail, bears N and SE
- 56.50 Cross Castaque Creek 30 lks. wide, course south.
- 75.78 Cross creek 30 lks. wide, course SW.
- 78.00 Leave Canada, bears NE and SW and ascend.
- 79.90 Intersect N & S. line 19 lks. south of corner to sections 14, 15, 22, 23, from which corner, I run S.  $89^{\circ}52'$  W., on a true line between sections 15 and 22.

Var.  $14^{\circ}25'$  E.

- 39.95 Set post 4 in. dia., 1 ft. in earth, 1 ft. above earth mound, 4 ft. in dia. at base, by 2 ft. in height and dug pit 24x18x12, 8 lks. north of  $\frac{1}{4}$  sec. cor.

- 79.90 The corner to sections 15, 16, 21, 22.

Land mountainous. Soil 2nd rate.

Timber and undergrowth of oak, sycamore, cottonwood, willow and chaparral.

---

North between sections 15 and 16.

Var.  $14^{\circ}25'$  E.

- 80.00 Set stone, 16x14x8, in stone mound,  $4\frac{1}{2}$  ft. in diameter at base by 2 ft. in height for corner to sections 9, 10, 15, 16.

Land mountainous. Soil 1st and 2nd rate.

Timber and undergrowth of oak and chaparral.

---

East on a random line between sections 10 and 15.

Var.  $14^{\circ}25'$  E.

Descend.

- 22.00 Cross head of gulch 10 lks. wide, course S.E. and ascend ridge.

- 40.00 Set temporary  $\frac{1}{4}$  sec. cor.

- 54.00 Leave ridge bears SE and NW and descend.
- 79.80 Intersect N and S. line 10 lks. north of corner to sections 10, 11, 14, 15, from which corner I run N.  $89^{\circ}56'$  W. on true line between sections 10 and 15.  
Var.  $14^{\circ}25'$  E.
- 39.90 Set post, 4 in. dia., 1 ft. in earth, 1 ft. above stone mound, 4 ft. in dia. at base, by 2 ft. in height, for  $\frac{1}{4}$  sec. cor.
- 79.80 The corner to sections 9, 10, 15, 16.  
Land mountainous.  
Soil 2nd rate.  
Timber and undergrowth of oak and chaparral.
- 
- North between sections 9 and 10.  
Var.  $14^{\circ}25'$  E.
- 
- 80.00 Set stone  $24 \times 12 \times 10$  in stone mound  $4\frac{1}{2}$  ft. in diameter at base, by 2 ft. in height, for corner to sections 3, 4, 9, 10.  
Land mountainous.  
Soil 1st and 2nd rate.  
Timber and undergrowth of oak and chaparral.  
April 30, 1880.
- 
- East on a true line between sections 3 and 10.  
Var.  $14^{\circ}25'$  E.
- Ascend.
- 29.00 Summit of spur, bears N and SW and descend.
- 80.00 Set stone  $14 \times 8 \times 7$  in stone mound, 4 ft. in dia. at base, by 2 ft. in height for  $\frac{1}{4}$  sec. cor.
- 60.50 Canada Castaque.

61.00 Cross trail in narrow Canada.

61.50 Cross creek 20 lks. wide, course south and ascend.

62.30 To foot of rocky bluff. Finding it impracticable to continue furth on this line, I set post 4 in. square 1 ft. in earth, 1 ft. above stone mound  $4\frac{1}{2}$  ft. in diameter at base, by 2 ft. in height, for witness to corner to sections 2, 3, 10, 11, from which bears a Cottonwood, 14 in. dia. N.  $78\frac{1}{2}^{\circ}$  W. 54 lks. dist. and make it a true line west.

Land mountainous. Soil 2nd rate.

Timber and undergrowth of oak, cottonwood and chaparral.