

TRANSCRIPT OF FIELD NOTES

Sections 28, 29, 30 and 31, Township 2 North, Range 8 West.

San Bernardino Meridian, California.

13	18				
24	19	20	21	22	
25	<sup>8</sup> 230	<sup>9</sup> 229	<sup>5</sup> 228	227	
36	<sup>6</sup> 131	<sup>7</sup> 632	<sup>4</sup> 433	334	T. 2 N.
	1	6	5	4	3 T. 1 N.

R. 9 W.  
R. 8 W.

T. 2 N., R. 8 W., S. B. M. (West Boundary)

From the established corner to Tps. 1 and 2 North, Ranges 8  
and 9 West, S. B. M. I run  
North between sections 31 and 36.

Variation 140° 26½' E.

Ascending.

- 38.00 Summit of spur bears southwest and thence along top of spur.  
40.00 Set a granite stone 15 x 7 x 8 ins. 10 ins. in the ground for  
¼ section corner marked ¼ on west face and raised a mound of  
stone alongside for ¼ sec. cor.  
80.00 Set sandstone 11 x 11 x 7 ins. 6 ins. in the ground for corner  
to sections 25, 30, 31 and 36, marked with 5 notches on the  
North and 1 notch on the South edges and raised a mound of  
stone alongside. Pits impracticable.

Land mountainous.

Soil second rate.

Timber scattering pine and oak.

Dense undergrowth of chaparral.

T. 2 N., R. 8 W., S. E. M. (West boundary)

North between sections 25 and 30.

Variation  $14^{\circ} 26\frac{1}{2}'$  E.

- 10.50 Summit of divide bears east and west about 500 feet above T. corner and descend along east slope of spur.
- 40.00 Set granite stone 14 x 9 x 8 ins. 9 ins. in the ground for  $\frac{1}{4}$  section corner marked  $\frac{1}{4}$  on west face and raised a mound of stone alongside. Pits impracticable.
- 67.00 Enter San Gabriel canyon, course west.
- 71.60 San Gabriel river 60 links wide, course west.
- 73.70 Leave San Gabriel canyon, course west and ascend along east slope of spur.
- 80.00 Set sandstone 20 x 11 x 9 ins. 15 ins. in the ground for the corner to sections 19, 24, 25 and 30. Marked with 4 notches on the north and 2 notches on the south edges and raised a mound of stone alongside. Pits impracticable.

Land mountainous.

Soil second rate.

Timber scattering pine and oak.

Dense undergrowth of chaparral.

---

Surveyed by G. W. Pearson, Deputy Surveyor, under his contract of December 10, 1883.

T. 2 N., R. 8 W., S. E. M.

From the corner to sections 3, 4, 33 and 34, on the south  
boundary of township I run

North between sections 33 and 34.

Variation  $14^{\circ} 26\frac{1}{2}'$  E.

80.00 Set granite stone 12 x 11 x 9 ins. 7 ins. in the ground for  
corner to sections 27, 28, 33 and 34, marked with 3 notches  
on the east and 1 notch on the south edges and raised mound  
of stone alongside. Pits impracticable.

Land mountainous.

Soil third rate.

Timber scattering pine and oak.

Dense undergrowth of chaparral.

---

North between sections 27 and 28.

Var.  $14^{\circ} 26\frac{1}{2}'$  E.

Ascend.

30.00 Top of ridge bears northwest and southeast and descend.

40.00 Set sandstone 16 x 9 x 9 ins. 11 inches in the ground for  $\frac{1}{4}$   
section corner marked  $\frac{1}{4}$  on west face and raised a mound of  
stone alongside. Pits impracticable.

80.00 Set granite stone 21 x 14 x 6 inches, 16 inches in ground  
for corner to sections 21, 22, 27 and 28, marked with 2  
notches on the south and 3 notches on the east edges and  
raised mound of stone alongside. Pits impracticable.

Land mountainous.

Soil third rate.

Timber scattering pine and oak.

Dense undergrowth of chaparral.

---

T. 2 N., R. 8 W., S. E. M.

From the established corner to sections 32, 33, 4 and 5, on south boundary of Tp. I run

North between sections 32 and 33.

Var.  $14^{\circ} 26\frac{1}{2}'$  E.

80.00 Set granite stone 19 x 11 x 5 ins. 14 inches in the ground for corner to sections 28, 29, 32 and 33, marked with 4 notches on the east and 1 notch on the south edges and raised a mound of stone alongside. Pits impracticable.

Land mountainous.

Soil third rate.

Timber pine and oak in ravine.

Dense undergrowth of chaparral.

---

East on a random line between sections 28 and 33.

Var.  $14^{\circ} 26\frac{1}{2}'$  E.

40.00 Set temporary  $\frac{1}{4}$  section corner.

80.63 Intersect north and south line at 39 links north of corner to sections 27, 28, 33 and 34.

Thence I run

North  $89^{\circ} 43'$  West on a true line between sections 28 and 33 with same variation.

Descend.

20.00 Ravine 30 links wide course northwest and ascend.

40.31 Set sand stone 17 x 9 x 9 inches, 12 inches in the ground for  $\frac{1}{4}$  section marked  $\frac{1}{4}$  on north face and raised mound of stone alongside. Pits impracticable.

55.00 Top of spur course north  $50^{\circ}$  west and descend.

80.63 The corner to sections 28, 29, 32 and 33.

Land mountainous.

Soil third rate.

Timber scattering pine and oak.

Dense undergrowth of chaparral.

T. 2 N., R. 8 W., S. 8. M.

North between sections 28 and 29.

Var.  $14^{\circ} 26\frac{1}{2}'$  E.

Ascend.

- 18.90 Top of spur bears north  $50^{\circ}$  west and descend.
- 29.60 Timbered ravine 30 links wide course northwest and ascend.
- 40.00 Set sandstone  $10 \times 9 \times 8$  inches, 6 inches in the ground for  $\frac{1}{4}$  section corner marked  $\frac{1}{4}$  on west face, and raised mound of stone alongside. Pits impracticable.
- 60.00 Top of spur bears north  $50^{\circ}$  west and descend.
- 80.00 Set granite stone  $19 \times 11 \times 5$  inches, 14 inches in the ground for corner to sections 20, 21, 28 and 29, marked with 4 notches on east and 2 notches on the south edges and raised mound of stone alongside. Pits impracticable.

Land mountainous.

Soil third rate.

Timber pine and oak in ravine.

Dense undergrowth of chaparral.

March 3, 1884.

---

East on a random line between sections 21 and 28.

Var.  $14^{\circ} 26\frac{1}{2}'$  E.

- 40.00 Set temporary  $\frac{1}{4}$  section corner.
- 80.00 Intersect north and south line at corner to sections 21, 22, 27 and 28.

Thence I run

West on a true line between sections 21 and 28, with same variation.

Descend gradually and along south bank of creek in Cow canyon.

- 40.00 Set granite stone  $13 \times 12 \times 7$  inches, 8 inches in the ground for  $\frac{1}{4}$  section corner marked  $\frac{1}{4}$  on north face, from which bears a sycamore 14 in. diameter north  $20^{\circ}$  west 17 links distant. Pine 16 in. diameter south  $39^{\circ}$  east 1.17 chains distant. Both marked  $\frac{1}{4}$  S. B. T.

T. 2 N., R. 8 W., S. E. M.

72.00 Leave canyon and ascend north slope of spur.

80.00 The corner to sections 20, 21, 28 and 29.

Land mountainous.

Soil second rate.

Timber, pine, oak and sycamore in canyon.

Dense undergrowth of chaparral.

---

From the established corner to sections 5, 6, 31 and 32 on  
south boundary of Township I run

North between sections 31 and 32.

Variation  $14^{\circ} 26\frac{1}{2}'$  E.

Ascending.

40.00 Set granite stone 14 x 9 x 6 inches, 9 inches in the ground for  
 $\frac{1}{4}$  section corner marked  $\frac{1}{4}$  on west face and raised a mound of  
stone alongside. Pits impracticable.

80.00 Set sandstone 14 x 9 x 8 inches, 9 inches in the ground for cor-  
ner to sections 29, 30, 31 and 32 marked with 1 notch on south  
and 5 notches on the east edges and raised mound of stone along-  
side. Pits impracticable.

Land mountainous.

Soil third rate.

Timber none.

Dense undergrowth of chaparral.

---

West on a random line between sections 30 and 31.

Var.  $14^{\circ} 26\frac{1}{2}'$  E.

40.00 Set temporary  $\frac{1}{4}$  section corner.

82.13 Intersect west boundary of township 23 links north of corner to  
sections 25, 30, 31 and 36.

Thence I run

North  $89^{\circ} 50'$  East on a true line between sections 30 and 31  
with same variation. Ascend.

T. 2 N., R. 8 W., S. E. M.

- 5.40 Summit of ridge bears north and south about 50 feet above section corner and descend.
- 42.13 Set sandstone 17 x 12 x 6 inches, 12 inches in the ground for  $\frac{1}{4}$  section corner marked  $\frac{1}{4}$  on north face and raised mound of stone alongside. Pits impracticable.
- 48.70 Ravine 60 links wide course north 5° west and ascend.
- 82.13 The corner to sections 29, 30, 31 and 32.  
Land mountainous.  
Soil third rate.  
Timber none.  
Dense undergrowth of chaparral brush.
- 

East on a random line between sections 29 and 32.

Var. 14° 26 $\frac{1}{2}$ ' E.

- 40.00 Set temporary  $\frac{1}{4}$  section corner.
- 80.26 Intersect north and south line 34 links south of corner to sections 28, 29, 32 and 33.  
Thence I run  
South 89° 45' West on a true line between section 29 and 32 with same variation. Descend.
- 5.80 Ravine 40 links wide course northwest and ascend.
- 40.13 Set sandstone 19 x 12 x 6 inches, 14 inches in the ground for  $\frac{1}{4}$  section corner marked  $\frac{1}{4}$  on north face and raised mound of stone alongside. Pits impracticable.
- 80.26 The corner to sections 29, 30, 31 and 32.  
Land mountainous.  
Soil third rate.  
Timber none.  
Dense undergrowth of chaparral.
-

T. 2 N., R. 8 W., S. B. M.

North between sections 29 and 30.

Var.  $140^{\circ} 26\frac{1}{2}'$  E.

Ascending.

- 11.60 Top of spur bears north  $40^{\circ}$  west and descend.
- 40.00 Set sandstone 16 x 11 x 9 inches, 11 inches in the ground for  $\frac{1}{4}$  section corner marked  $\frac{1}{4}$  on west face and raised mound of stone alongside. Pits impracticable.
- 63.20 Enter canyon of the Cow creek course West.
- 73.15 Cow creek 40 links wide course west.
- 73.25 Leave canyon course west and ascend abruptly.
- 80.00 Set granite stone 12 x 11 x 8 inches, 7 inches in the ground for corner to sections 19, 20, 29 and 30 marked with 2 notches on south and 5 notches on east edges; from which bears a

Pine 22 inches diameter North  $71^{\circ}$  east 1.09 chs. distant, marked T. 2 N., R. 8 W., Section 20 B. T.  
Pine 18 inches diameter North  $47^{\circ}$  west 94 links distant, marked T. 2 N., R. 8 W., Section 19 B. T.  
Pine 10 inches diameter South  $81^{\circ}$  west 78 links distant, marked T. 2 North, R 8 West, Section 30 B. T.  
Pine 14 inches diameter South  $14^{\circ}$  East, 66 links distant, marked T 2 North, R. 8 West, Section 29 B. T.

Land mountainous.

Soil third rate.

Timber pine and oak in canyon.

Dense undergrowth of chaparral.

---

West on a random line between sections 19 and 30.

Var.  $140^{\circ} 26\frac{1}{2}'$  E.

- 40.00 Set temporary  $\frac{1}{4}$  section corner.
- 82.88 Intersect west boundary of township 47 links north of corner to sections 19, 24, 25 and 30.
- Thence I run  
North  $89^{\circ} 40'$  east on a true line between sections 19 and 30 with same variation. Descend.
- 21.00 Enter San Gabriel canyon course south  $10^{\circ}$  west.

T. 2 N., R. 8 W., S. E. M.

- 21.70 San Gabriel river 60 links wide course south 10° west.  
25.60 Leave canyon course south 10° west and ascend.  
42.88 Set granite stone 17 x 9 x 8 inches, 12 inches in the ground for  
¼ section corner marked ¼ on north face and raised mound of stone  
alongside. Pits impracticable.  
47.60 Point of spur bears southwest and descend.  
52.88 The corner to sections 19, 20, 29 and 30.  
Land mountainous.  
Soil third rate.  
Timber pine and oak in ravine.  
Dense undergrowth of chaparral brush.
- 

East on a random line between sections 20 and 29.

Var. 14° 26½' E.

- 40.00 Set temporary section corner.  
50.15 Intersect north and south line 41 links south of corner to  
sections 20, 21, 28 and 29. Thence I run  
South 89° 42' west on a true line between sections 20 and 29  
with same variation. Ascend.  
22.60 Point of spur bears northwest and descend.  
40.09 Set granite stone 13 x 11 x 7 inches, 8 inches in the ground  
for ¼ section corner marked ¼ on north face, from which bears  
an  
Oak 14 inches in diameter south 19° east 42 lks. distant.  
Pine 18 inches diameter south 22° west 93 links distant.  
Both marked ¼ S. B. T.  
41.60 Enter Cow canyon course south.  
47.00 Creek 12 links wide course south.  
48.15 Leave canyon course south and ascend.  
50.15 The corner to sections 19, 20, 29 and 30.  
Land mountainous.  
Soil second rate.  
Timber pine and oak in canyon.  
Dense undergrowth of chaparral.
- 

Surveyed by G. W. Pearson, Deputy Surveyor, under his contract  
of December 10, 1853