

E. B. Tp. 1 S. R. 14 W. S. B. M.

Chains

Begin at the cor. to Secs. 1-6-7-12 T. 1 S. Rgs. 13 and 14
W. San Bernardino Co., retracing and run north between
Sections 1 and 6,
Va. 15°05' E.

40.00 To a mound of earth at the established 1/4 sec. cor. Set
a Redwood post 4 feet long and 3 x 3 in. 20 in. deep and
raised the mound 2 ft. high with a 24 in. base.
50.00 To a dry wash 15 lks. wide course S. E.
52.00 Foot of hill bearing E and W. and ascend.
61.00 Summit of hill 50 lks. west of its S. E. point.
62.00 Cross summit and descend.
66.00 Foot of hill bearing N. W. and S. E.
67.00 To road bearing N. W. and S. E.
71.00 Cross main valley bearing N. W. and S. E. and enter a small
valley 5 chs. wide.
77.00 Foot of Ridge S. 10° W. and ascend across its steep East
Slope.
80.00 Set a sand rock 20 x 16 x 12, and raised a mound of sand rock
30 inches high and with a base of 36 inches for cor. to
Tps. 1 N. and 1 S. Rgs. 13 and 14 W.
The stump of an Evergreen Red Oak 16 in. in diam. bears
S. 11 W. 5.76 chs. dist.
Soil 2nd rate.
This mile is in Rancho Los Felis.

South Endy. Tp. 1 N. R. 14 W. S. B. M.

chains

West on the S. Endy. of Section 36.
Va. 15°05' E.

2.00 Summit of Ridge S. 10° W.
5.00 Foot of Ridge.
8.00 Cross narrow valley bears south.
10.00 Top of low Ridge N. and S.
15.00 Enter narrow valley bears S. 80° E.
29.00 Cross valley and ascend steep hill.
31.75 Old mound of rock and earth the stump of an Evergreen Red
Oak 20 in. dia. and 4 feet high bears S. 26° W. 155 lks. dist.
38.50 Summit of hill north and south.
39.00 Cross summit and descend.
40.00 Set a sand rock 14 x 10 x 8 in a mound of sand rock 30 in.
high and 2 ft. base for 1/4 sec. cor.
50.00 Foot of hill at Ravine bearing S. W.
51.50 Cross Ravine and ascend spur.
60.00 Summit of spur bearing S. W.
65.00 Foot of spur and enter a narrow valley bearing S. 10° W.

72.00 Cross valley and ascend low Ridge.
 75.00 Summit of Ridge N. and S.
 76.00 Cross summit and descend into head of ravine.
 80.00 Set sand rock 18 x 14 x 9 and raised mound of sand rock with a base of 3 feet and 30 in. high for cor. to sess. 35 and 36 on the West Bndy. of Rancho Los Felis
 Land broken, mountainous and heavily timbered scrub and Chaparral Oak.
 Soil 3rd rate.

S. B. Tp. 1 N. R. 14 W. S. B. M.

Chains

West. on the S. Bndy. of Section 35.
Va. 15°05' E.

1.00 To a dry wash 10 lks. wide S. 80 W.
 3.00 Leave Canyon and run along the South slope of hills.
 17.00 Foot of Ridge and ascend.
 22.00 Top of Ridge S. 25° W. and descend.
 30.00 Foot of Ridge and to road N. and S.
 32.20 Cross dry ravine 20 lks. wide bearing South.
 34.50 Cross point of Ridge, bearing N. W.
 35.00 Enter dry Ravine 80 lks. wide runs S. 85° E. and run up same.
 38.80 Set a sand rock 14 x 10 x 6 on the S. and left bank of Ravine and raised a mound of sand rock 30 in. high and 2 feet base at the foot of a steep Ridge for 1/4 sec. witness corner.
 45.00 To summit of Ridge, bearing N. and S.
 46.00 Cross summit and descend.
 50.50 Foot of Ridge and enter narrow valley, bears S.
 51.60 The S. W cor. of Honey refining house north 2 lks. (of H. Olansen)
 58.00 Leave valley and ascend. spur of ridge bears W.
 70.50 Summit of main Ridge N. and S.
 77.00 Descend steep W. slope of main Ridge.
 80.00 Set a sand rock 20 x 14 x 10 in. deep and raised a mound of Sand Rock 30 inches high and 3 feet base for corner to sections 34 and 35.
 Land broken and hilly with thick scrub and chaparral Oak.
 Soil 3rd rate.

S. B. Tp. 1 N. R. 14 W. S. B. M.

Chains

West. on South Bndy. of Section 34.
Va. 15°05' E.

6.00 Cross dry ravine 20 lks. wide, course N. 60° W.
 19.50 Cross dry ravine 20 lks. wide bears S. 30° W.
 Ascend hill.
 House of Ewer bears S. 10° E. about 10 chains.
 22.50 Top of ascent Ridge bears N. and S. descend.
 27.00 Foot of descent, cross wash 10 lks. wide and ascend.
 38.00 Top of ascent high Ridge bears N. and S. and descend.
 40.00 Set 1/4 sec. cor. rock 7 x 9 x 15 inches 6 in. deep in a mound of rock 30 inches sq. at base and 24 in. high from which house of John Donaldson bears S. 10° W.
 16 chains dist.

Chains

42.50 Foot of descent cross gulch 10 lks. wide course south ascend along S. slope of hill.

48.00 Top of ascent Ridge bears South descend.

53.00 Foot of descent cross road in Cahuenga Pass bearing N. 40° W. and S. 40° E.

54.00 Cross Cahuenga Pass and ascend steep brushy and broken hills.

57.00 Top of ascent Ridge bears N. 65° W. and S. 65° E. thence along its southerly slope descending.

67.00 Foot of descent cross ravine 2 lks. wide course S. 65° E. ascend along northerly slope of Ridge.

75.00 Top of ascent Ridge bears N. 65° W. and S. 65° E. Finding that it would be impracticable to set a corner at 80 chs. I set a witness corner at

76.00 On the brow of summit and marked a sand stone rock 18 x 20 x 24 inches and constructed a mound of stone 3 feet. sq. and 24 inches high for witness corner to Sections 33 and 34 and ran along the steep S. Slope of Ridge.

80.00 True point for corner to Secs. 33 and 34. Found it impossible to build a corner at this point. Land broken and hilly. Soil 3rd rate.

S. E. T. 1 N. R. 14 W. S. B. M.

Chains

West, on the S. Bndy. of Section 33, from true corner.

Va. 15° 05' E.

5.00 Foot of descent cross Ravine 50 lks. wide, bears S. 65° E. ascend.

12.00 Top of ascent. Ridge bears N. W. and S. E. descend.

18.00 Foot of descent and enter valley course S. E.

36.00 Leave valley and ascend.

38.00 Top of Ridge in low gap bears N. and S. descend.

40.00 Raised a mound of stone for 1/4 Sec. Cor. 3 feet square 20 in. high. Va. 14° 45' E.

46.00 Foot of descent and ran along the north face of Ridge.

62.00 To deep ravine 80 lks. wide. Course south and ascend.

67.00 Top of ascent, Ridge bears E. and W. ran along same.

71.00 Leave top of ridge descend across south slope.

80.00 Raised a mound of Rock for corner to Sections 32 and 33 3 feet square 30 inches high. Land broken and hilly. Soil 2nd rate.

S. E. T. 1 N. R. 14 W. S. B. M.

Chains

West, on South Bndy. of Section 32.

Va. 14° 55' E.

10.00 Foot of descent cross Ravine 50 lks. wide, course S. E. and ascend.

Chains

15.00 Top of ascent, Ridge bears S. E.
Descend.
18.00 Foot of descent, cross Ravine 40 lks. wide, course S. 60° E.
Ascend.
26.00 Top of ascent, Ridge bears S. 60° E.
Descend.
30.00 Foot of descent, cross Ravine 60 lks. wide, course S. 65° E.
Ascend.
36.00 Top of ascent, Ridge bears S. 65° E.
39.00 Descend.
40.00 Raised a mound of stone 30 inches square 20 inches high for
1/4 sec. cor.
47.00 Foot of descent, cross Ravine 60 lks. wide, course S. 70° E.
Ascend.
60.00 Top of ascent, Ridge bears N. W. and S. E. Descend.
72.00 Foot of descent cross Ravine 70 lks. wide, course south.
Ascend steep hill.
80.00 Raised a mound of sand rock with a 3 foot base 30 inches
high for corner to Sections 31 and 32.
Land very broken and mountainous.
Soil 3rd rate.

S. B. T. 1 N. R. 14 W. S. B. M.

Chains

West, on South Endy, of Section 31.

Va. 15°00' E.

22.00 Leave east slope of hill and run across steep north slope of
same about 5 chains from summit bearing south.
30.00 To gorge in N. face of mountain running North 2 chains wide.
34.00 Leave north slope of mountain and descend west slope in
dense chaparral.
40.00 Raised a mound of Rock 30 in. sq. 24 inches high for 1/4
Sec. corner.
56.50 Foot of descent and to a Ravine 50 lks. wide bears N. 70° W.
68.00 Foot of steep west slope of mountain.
74.00 Cross Ravine 50 lks. wide, course N. W.
80.00 To the rock mound as the established cor. to
T. 1 N. and 1 S. Rs. 14 and 15 W.
Secs. 31 and 36. 1 and 6
Land broken, Mountainous. last 1/2 mile heavy brush.
Soil 2nd rate.
Survey completed 3rd day of July 1879.