



Copied from Photographic Copies
furnished by
U. S. General Land Office
Washington D. C.

R. 11 W.					
19 <small>11</small>	¹² 20 <small>11</small>	⁹ 21 <small>8</small>	⁶ 22 <small>6</small>	⁴ 23 <small>4</small>	² 24 <small>2</small>
30 <small>10</small>	¹⁰ 29 <small>10</small>	⁸ 28 <small>7</small>	⁶ 27 <small>5</small>	³ 26 <small>3</small>	¹ 25 <small>1</small>
31 <small>9</small>	⁹ 32 <small>9</small>	⁷ 33 <small>7</small>	⁵ 34 <small>5</small>	³ 35 <small>3</small>	¹ 36 <small>1</small>
6	5	4	3	2	1

T. 2 N.

T. 2 N. R. 11 W. S. B. M.

From the established corner to sections 1-2-35 and 36 on the south boundary of township I run north $0^{\circ} 12'$ east on a true line between sections 35 and 36.

Var. $14^{\circ} 29'$ East.

- Descend.
5.20 Ravine 40 lks. wide course N. 80° E. and ascend.
20.00 Top of spur bears N. 80° E. and descend.
36.00 Gulch 30 lks. wide course N. 60° E. and ascend.
40.00 Set post 4 x 4 ins. 4 feet long and deep marked stone 12 ins. in the ground for 1/4 section corner marked 1/4 S. on the W. face and raised mound of stone alongside.
Pits impracticable.
80.00 Set granite stone 11 x 10 x 9 ins. 6 ins. in the ground for corner to sections 25-26-35 and 36 marked with 1 notch on the S. and E. edges and raised mound of stone alongside.
Pits impracticable.
Land mountainous.
Soil 3rd rate.
Timber some.
Dense undergrowth of chaparral.

East on a random line between sections 25 and 36.
Var. $14^{\circ} 29'$ East

- 40.00 Set a temporary 1/4 section corner.
80.54 Intersect east boundary of township 59 lks. S. of the corner to sections 25-30-31 and 36
Thence I run
S. $89^{\circ} 35'$ west on a true line between sections 25 and 36 with same variation.
17.00 Ravine 40 lks. wide course N. E. and ascend.
40.27 Set granite stone 14 x 9 x 8 ins. 9 ins. in the ground for 1/4 section corner marked 1/4 on N. face and raised mound of stone alongside.
Pits impracticable.
80.54 The corner to sections 25-26-35 and 36.
Land Mountains.
Soil 3rd rate.
Timber Pine and Oak in ravine.
Dense undergrowth of Chaparral.

N. $0^{\circ} 12'$ East on a true line between sections 25 and 26.
Var. $14^{\circ} 29'$ East.

- 10.00 Summit of ridge bears N. E. and S. W. and descend.
40.00 Set sand stone 12 x 9 x 6 ins. 7 ins. in the ground for 1/4 section corner marked 1/4 on West face, and raised mound of stone alongside.
Pits impracticable.
59.00 Gulch 30 lks. wide course N. E. and ascend.

T. 2 N. R. 11 W. S. B. M.

80.00 Set granite stone 13 x 12 x 10 ins. 8 ins. in the ground for corner to sections 23 x 24 x 25 and 26 marked with 2 notches on the S. and 1 notch on the E. edges and raised mound of stone alongside.
Pits impracticable.
Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

East on a random line between sections 24 and 25.
Var. 14° 29' East.

40.00 Set temporary 1/4 section corner.
80.47 Intersect east boundary of Tp. 28 lks. south of corner to sections 19-24-25 and 30.
Thence I run
S. 89°45' W. on a true line between sections 24 and 25 with same variation.
Ascend.
8.50 Top of spur bears N. 15° E. and S. 40° W. and descend.
20.00 Gulch 10 lks. wide near head course N. 10° E. and ascend.
38.00 Top of spur bears N. 10° E. and descend.
40.24 Set sand stone 19 x 11 x 9 ins. 14 ins. in the ground for 1/4 section corner marked 1/4 on N. face and raised mound of stone alongside.
Pits impracticable.
61.00 Gulch 50 lks. wide course north and ascend.
80.47 The corner to sections 23-24-25 and 26.
Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of chaparral

North on a random line between sections 23 and 24.
Var. 14°29' East.

40.00 Set a temporary 1/4 section corner.
80.31 To a point 62 lks. west of corner to sections 13-14-23 and 24 which is a well preserved post 4 x 4 ins. firmly set in large mound of rocks marked Tp. 2 N. R. 11 W. Sec. 13 on the N. E. section 24 on the S. E.
Section 23 on the S. W. and
Section 14 on the N. W. faces
Thence I run
S. 0°27' west on a true line between sections 23 and 24 with same variation.
Ascend.
30.00 Top of spur bears N. E. and descend.
40.16 Set granite stone 23 x 14 x 7 ins. 18 ins. in the ground for 1/4 section corner marked 1/4 on W. face and raised mound of stone alongside.
Pits impracticable.
80.31 The corner to sections 23-24-25 and 26.
Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

T. 2 N. R. 11 W. S. E. M.

From the corner to sections 2-3-34 and 35 I run
North 0° 12' East on a true line between sections 34 and 35.
Va. 14° 29' East.

- Ascend.
- 19.25 Summit of divide between San Gabriel and Santa Anita bears
N. 75° W. and S. 75° E. and descend.
- 40.00 Set granite stone 18 x 12 x 9 ins. 13 ins. in the ground for
1/4 section corner marked 1/4 on W. face and raised mound of
stone alongside.
Pits impracticable.
- 59.00 Gulch 30 lks. wide course N. W. and ascend.
- 80.00 Set sand rock 18 x 14 x 10 ins. 13 ins. in ground for
corner to sections 26-27-34 and 35 marked with 1 notch on
the S. and 2 notches on the E. edges and raised mound of
stone alongside.
Pits impracticable.
Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

East on a random line between sections 26 and 35.
Var. 14° 29' East.

- 40.00 Set temporary 1/4 section corner.
- 80.60 Intersect N. and S. line 37 lks. N. of corner to sections
25-26-35 and 36
Thence I run
N. 89° 44' West on a true line between sections 26 and 35
with same variation and ascend.
- 11.60 Summit of ridge bears N. E. and S. E. and descend.
- 30.00 Head of gulch course N. 10° E. and ascend.
- 40.30 Set granite stone 12 x 10 x 9 ins. 7 ins. in the ground
for 1/4 section corner marked 1/4 on N. face and raised
mound of stone alongside.
Pits impracticable.
- 41.00 Summit of ridge bears N. and S. and descend.
- 80.60 The corner to sections 26-27-34 and 35.
Land mountainous.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

North 0° 12' East on a true line between sections 26 and 27.
Var. 14° 29' E.

- Ascend.
- 40.00 Set granite stone 12 x 12 x 9 ins. 7 ins. in the ground for
1/4 section corner marked 1/4 on W. face and dug pits 18 x
18 x 12 ins. N. and S. of stone 5-1/2 feet dist. and
raised mound of earth 1-1/2 feet high, 3-1/2 feet base
alongside.
- 72.60 Top of spur bears N. W. and descend.
- 80.00 Set sand stone 11 x 11 x 9 ins. 6 ins. in the ground for
corner to sections 22-23-26 and 27 marked with 2 notches on
E. and S. edges and dug pits 18 x 18 x 12 ins. in each
section 5-1/2 feet distance and raised mound of earth 2-1/2

T. 2 N. R. 11 W. S. B. M.

feet high 4-1/2 feet base alongside.
Land mountains.
Soil 2nd rate.
Timber none.
Dense undergrowth of Chaparral.

April 18th 1884.

East on a random line between sections 23 and 26.
Var. 14° 29' East.

40.00 Set temporary 1/4 section corner.
80.41 Intersect N. and S. line 27 lks. S. of corner to sections
23-24-25 and 26
Thence I run
S. 89° 48' West on a true line between sections 23 and 26
with same variation.
Ascend.
28.40 Summit of ridge bears N. 10° W. and S. 10° E. and descend.
40.20 Set post 4 x 4 ins. and deep marked stone 12 ins. in the
ground for 1/4 Section Corner marked 1/4 on N. face and
dig pits 18 x 18 x 12 ins. E. and W. of post 5-1/2 feet
dist. and raised mound of earth 1-1/2 feet high 3-1/2 feet
base alongside.
66.00 Ravine 80 lks. wide course north and ascend.
80.41 The corner to sections 22-23-26 and 27.
Land Mountains.
Soil 3rd rate.
Timber, Pine and Oak in ravine.
Dense undergrowth of Chaparral.

North on a random line between sections 22 and 23.
Var. 14° 29' East.

40.00 Set temporary 1/4 section corner.
80.43 To a point 37 lks. west of corner to sections 14-15-22
and 23 which is a post 4 x 4 ins. marked with Tp. 2 N.
R. 11 W. Section 14 on N. E. section 23 on S. E. section 22
on S. W. and section 15 on N. W. faces, firmly set in mound
of rocks,
from which bears a Live Oak 16 ins. in diam.
N. 27-1/2° E. 29 lks. dist.
Thence I run
S. 0° 16' West on a true line between sections 22 and 23
with same variation.
Ascending.
26.70 Point of spur bears N. W. and descend.
40.21 Set sand stone 12 x 11 x 7 ins. 7 ins. in the ground for 1/4
section corner marked 1/4 on W. face and raised mound of
stone alongside.
Pits impracticable.
60.50 Gulch 80 lks. wide course N. W. and ascend.
80.43 The corner to sections 22-23-26 and 27.
Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

T. 2 N. R. 11 W. S. B. M.

From the corner to sections 3-4-33 and 34 on the south
boundary of Tp. 1 run
North $0^{\circ}12'$ East between sections 33 and 34
Var. $14^{\circ}29'$ East

Ascend

40.00 Set granite stone 26 x 11 x 4 ins. 18 ins. in the ground for
1/4 section corner marked 1/4 on west face and raised mound
of stone alongside.
Pits impracticable.

43.20 Summit of divide bears N. 85° W. and S. 85° E. and descend.

66.00 Enter timber bears N. W. and S. E.

80.00 Set post 6 x 6 ins. 4-1/2 feet long with marked stone 12 ins.
in the ground for corner to sections 27-28-33 and 34 marked
Tp. 2 N. section 27 on N. E.
R 11 W. section 34 on S. E.
Section 33 on the S. W. and section 28 on the N. W. faces
from which a
Pine bears N. 31° E. 67 lks. dist. 14 ins. diam marked
T. 2 N. Section 27 B.T.
Pine 16 ins. diam. bears S. $11-1/4^{\circ}$ E. 1.11 chs. dist.
marked R. 11 W. section 34 B. T.
Pine 18 ins. diam. bears S. 23° W. 91 lks. dist. marked
section 33 B. T.
Pine 26 ins. diam. bears N. 42° W. 43 lks. dist. marked
section 28 B. T.
Land mountainous.
Soil 1st and 3rd rate.
Timber Pine and Oak.
Dense undergrowth of Chaparral brush.

East on a random line between sections 27 and 34.
Var. $14^{\circ}29'$ East.

40.00 Set temporary 1/4 section corner.

80.55 Intersect N. and S. line 30 lks. N. of corner to sections
26-27-34 and 35
Thence I run
N. $89^{\circ}44'$ west on a true line between sections 27 and 34 with
same variation.

Descend.

17.00 Gulch 35 lks. wide course N. and ascend.

40.27 Set granite stone 15 x 11 x 7 ins. 10 ins. in the ground
for 1/4 section corner marked 1/4 on N. face and raised
mound of stone alongside.
Pits impracticable.

70.00 Summit of ridge bears N. and S. and descend.

73.20 Enter timber bears N. and S.

80.55 The corner to sections 27-28-33 and 34.
Land mountains.
Soil 3rd rate.
Timber 6.80 chs.
73.20 chs. dense undergrowth of chaparral.

T. 2 N. R. 11 W. S. B. M.

North $0^{\circ}12'$ East between sections 27 and 28.
Var. $14^{\circ}29'$ East.

- 40.00 Descend along spur.
Set sand stone 12 x 10 x 9 ins. 7 ins. in the ground for
1/4 section corner marked 1/4 on W. face,
from which bears a
Pine 14 ins. diam. N. 15° E. 69 lks. dist. marked 1/4 S.B.T.
Pine 28 ins. diam. bears S. 19° W. 85 lks. dist. marked 1/4
S. B. T.
- 40.50 Top of spur bears N.
Thence along summit and west slope of spur.
- 73.00 Leave timber bears E. and W.
- 80.00 Set granite stone 20 x 11 x 10 ins. 15 ins. in the ground for
corner to sections 21-22-27 and 28 marked with 2 notches in
the S. and 3 notches on the E. edges and raised mound of stone
alongside.
Pits impracticable.
Land 73 chs. timber and mountains.
Soil 2nd rate.
7.00 Dense undergrowth of Chaparral.

East on a random line between sections 22 and 27.
Var. $14^{\circ}29'$ East.

- 40.00 Set temporary 1/4 section corner.
80.42 Intersect N. and S. line 30 lks. N. of corner to sections
22-23-27- and 26
Thence I run
N. $89^{\circ}47'$ west on a true line between sections 22 and 27.
Ascend.
- 10.00 Top of spur bears N. 20° W. and descend.
29.00 Gulch 30 lks. wide course W. and ascend.
40.21 Set granite stone 16 x 11 x 8 ins. 11 ins. in the ground for
1/4 section corner marked 1/4 on N. face and raised mound of
stone alongside.
Pits impracticable.
- 80.42 The corner to sections 21-22-27 and 28.
Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

North on a random line between sections 21 and 22 retracing
40 chs.
Va. $14^{\circ}29'$ East.

- 40.00 Unable to find old corner.
Set temporary 1/4 section corner.
80.00 To a point 26 lks. west of corner to sections 15-16- 21 and
22 which is a post greatly decayed in mound of rocks
partially destroyed. I rebuilt corner by setting sand stone
12 x 9 x 6 ins. 7 ins. in the ground for corner to sections
21-22-15 and 16 marked with 3 notches on the S. and E edges
and raised mound of stone alongside.
Pits impracticable.

T. 2 N. R. 11 W. S. B. M.

Thence I run
S. 0° 11' west on a true line between sections 21 and 22
with same variation.
Ascend.
40.00 Set granite stone 16 x 11 x 5 ins. 11 ins. in the ground
for 1/4 section corner marked 1/4 on N. face and raised
mound of stone alongside.
Pits impracticable.
80.00 The corner to sections 21-22-27 and 28.
Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

From the corner to sections 32 and 33 I run
N. 0° 12' east on a true line between sections 32 and 33
Var. 14° 29' East.
Ascending.
21.50 Enter timber bears E. and W.
40.00 Set a sand stone 15 x 11 x 8 ins. 10 ins. in the ground
for 1/4 section corner marked 1/4 on W. face
from which bears a
Pine 19 ins. diam. N. 30° W. 75 lks. dist. marked 1/4 S.B.T.
Pine 26 ins. diam. S. 20° W. 32 lks. dist. marked 1/4 S.B.T.
and raised mound of stone alongside.
56.00 Summit of divide bears E. and W. and descend.
65.70 Leave timber bears E. and W.
78.00 Gulch 30 lks. wide course N. E. and ascend.
80.00 Set granite stone 18 x 11 x 7 ins. 13 ins. in the ground
for corner to sections 28-29-32 and 33 marked with 1 notch
on the S. and 4 notches on the E. edges and raised mound of
stone alongside.
Pits impracticable.
Land mountains.
Timber 44.20 chs.
Dense undergrowth of Chaparral, 35.80 chs.
Soil 2nd and 3rd rate.

East on a random line between sections 28 and 33
Var. 14° 29' East.
40.00 Set temporary 1/4 section corner.
80.52 Intersect N. and S. line 21 lks. S. of corner.
Thence I run
S. 89° 51' west on a true line between sections 28 and 33
with same variation.
Descend.
14.10 Leave timber bears N. and S.
18.10 Gulch 30 lks. wide course N. W. and ascend.
40.26 Set granite stone 13 x 12 x 11 ins. 8 ins. in the ground
for 1/4 section corner marked 1/4 on W. face and raised
mound of stone alongside.
Pits impracticable.
46.40 Top of ridge bears N. and S. and descend.
78.20 Gulch 30 lks. wide course W. and ascend.
80.52 The corner to sections 28-29-32 and 33.
Land mountains.

T. 2 N. R. 11 W. S. B. M.

Soil 3rd rate.
Timber Pine.
Dense undergrowth of Chaparral.

April 19th 1884.

N. 0°12' E. between sections 28 and 29
Var. 14°29' East.

Ascend
40.00 Set granite stone 14 x 9 x 8 ins. 9 ins. in the ground for
1/4 section corner marked 1/4 on W. face and raised mound
of stone alongside.
Pits impracticable.
74.75 Point of spur bears N. E. and descend.
80.00 Set granite stone 16 x 11 x 10 ins. 11 ins. in the ground
for corner to sections 20-21-28 and 29 marked with 2 notches
on S. and 4 notches on E. edges raised mound of stone
alongside.
Pits impracticable.
Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

East on a random line between sections 21 and 28
Var. 14° 29' East.

40.00 Set temporary 1/4 section corner.
80.40 Intersect N. and S. line 28 lks. N. of corner to sections
21-22-28 and 27
Thence I run
N. 89° 48' W. on a true line between sections 21 and 28
with same variation.
Descend.
22.80 Gulch 40 lks. wide course N. 20° W. and ascend.
40.20 Set granite stone 19 x 12 x 8 ins. 14 ins. in the ground
for 1/4 section corner marked 1/4 on N. face and raised
mound of stone alongside.
Pits impracticable.
42.00 Top of spur bears N. and descend.
63.50 Gulch 60 lks. wide course N. and ascend.
80.40 The corner to sections 20-21-28-and 29.
Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

T. 2 N. R. 11 W. S. B. M.

North on a random line between sections 20 and 21 retracing
40 chs.

Var. 14° 29' East.

40.00 After diligent search being unable to find 1/4 section corner
I set temporary 1/4 section corner.

80.37 To a point 3/4 lks. west of corner to sections 16-17-20 and
21 which is a well preserved post firmly set in mound of
rocks marked Tp. 2 N. R. 11 W. section 16 on N. E. section
21 on S. E. section 20 on S. W. and section 17 on N. W. faces.

from which bears
An Alder tree 8 ins. diam. N. 18-1/2° W. 60 lks. dist.
marked Tp. 2 N. R. 11 W. section 17 B. T.

Thence I run

S. 0° 15' west on a true line between sections 20 and 21
with same variation.

Ascending.

40.18 Set granite stone 19 x 11 x 7 ins. 14 ins. in the ground for
1/4 section corner marked 1/4 on W. face and raised mound
of stone alongside.

Pits impracticable.

80.37 The corner to sections 20-21-28- and 29.

Land mountains.

Soil 3rd rate.

Timber none.

Dense undergrowth of Chaparral.

From the corner to sections 5-6-31 and 32 on the S.
boundary of the township

I run

N. 0° 12' E. between sections 31 and 32

Var. 14° 29' East

Ascend.

38.50 Summit of ridge bears E. and W. and descend.

40.00 Set granite stone 16 x 11 x 9 ins. 11 ins. in the ground
for 1/4 section corner marked 1/4 on W. face and raised
mound of stone alongside.

63.00 Gulch 40 lks. wide course S. W. and ascend.

80.00 Set sand stone 22 x 11 x 6 ins. 17 ins. in the ground for
corner to sections 29-30-31 and 32 marked with 5 notches
on E. and 1 notch on the S. edges and raised mound of stone
alongside.

Pits impracticable.

Land mountainous.

Soil 3rd rate.

Timber none.

Dense undergrowth of Chaparral.

T. 2 N. R. 11 W. S. B. M.

East on a random line between sections 29 and 32
Var. 14° 29' East.

40.00 Set temporary 1/4 section corner.
80.60 Intersect N. and S. line 49 lks. N. of corner to sections
28-29-32 and 33
Thence I run
N. 89°39' west on a true line between sections 29 and 32
with same variation.
Ascend.

40.30 Set granite stone 19 x 12 x 6 ins. 14 ins. in ground for 1/4
section corner marked 1/4 on N. face and raised mound of
stone alongside.
Pits impracticable.

42.00 Enter timber bears N. and S.
50.90 Summit of divide bears N. and S. and descend.
51.20 Wilsons trail bears N. and S.
71.80 Gulch 20 lks. wide course S. and ascend.
73.00 Leave timber N. and S.
80.60 The corner to sections 29-30-31 and 32.
Land mountains.
Soil 3rd rate.
Timber Pine.
Dense undergrowth of Chaparral.

April 21st 1884.

As this line can only be run a portion of the distance
I run
West on a true line between sections 30 and 31.
Var. 14° 29' East.

40.00 Ascending.
Set a granite stone 16 x 11 x 7 ins. 11 ins. in the ground
for 1/4 section corner marked 1/4 on N. face and raised
mound of stone alongside.
Pits impracticable at foot of very steep ascent.
It being impracticable to measure the line any farther I
drop the line at this point.
Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

N. 0°12' E. between sections 29 and 30.
Var. 14°29' East.

16.70 Ascend.
40.00 Summit of divide bears E. and W. and descend.
Set sand stone 13 x 10 x 6 ins. 8 ins. in the ground for 1/4
section corner marked 1/4 on N. face and raised mound of
stone alongside.
Pits impracticable.

64.30 Gulch 40 lks. wide course N. E. and ascend.
80.00 Set granite stone 16 x 11 x 9 ins. 11 ins. in the ground for
corner to sections 19-20-29 and 30 marked with 2 notches
on S. and 5 notches on the E. edges and raised mound of stone
alongside.
Pits impracticable.

T. 2 N. R. 11 W. S. B. M.

Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

East on a random line between sections 20 and 29
Var. 14°29' East.

40.00 Set temporary 1/4 section corner.
80.29 Intersect N. and S. line 40 lks. N. of corner to sections
20-21-28 and 29
Thence I run
N. 89°43' west on a true line between sections 20 and 29
with same variation.
Ascend.
40.15 Set granite stone 14 x 9 x 8 ins. 9 ins. in the ground
for 1/4 section corner marked 1/4 on N. face and raised
mound of stone alongside.
Pits impracticable.
47.00 Trail bears N. and S.
47.60 Top of spur bears N. and descend.
68.50 Gulch 40 lks. wide course N. 20° E. and ascend.
80.29 The corner to sections 19-20-29 and 30.
Land mountains.
Soil 3rd rate.
Timber none.
Dense undergrowth of Chaparral.

West on a random line between sections 19 and 30
Var. 14° 29' East.

40.00 Set temporary 1/4 section corner.
80.32 Intersect west boundary of township 27 lks. N. of corner
to sections 19-24-25 and 30 which is a post greatly decayed
in earth mound with pits nearly destroyed. I rebuilt corner
by setting granite rock 16 x 12 x 10 ins. 11 ins. in the
ground for corner to sections 19-24-25 and 30 marked with
4 notches on N. and 2 notches on S. edges and redug pits and
rebuilt earth mound around stone
Thence I run
N. 89°48' E. on a true line between sections 19 and 30 with
same variation.
Ascending.
40.32 Set granite stone 10 x 11 x 6 ins. 13 ins. in the ground
for 1/4 section corner marked 1/4 on N. face and raised
mound of stone alongside.
Pits impracticable.
On summit of spur bears N. E. and descend.
80.32 The corner to sections 19-20-29 and 30.
Land mountains.
Soil 3rd rate.
Timber none
Dense undergrowth of Chaparral.

T. 2 N. R. 11 W. S. B. M.

North on a random line between sections 19 and 20
Var. 14° 29' East.

- 40.00 Set temporary 1/4 section corner.
80.28 To a point 26 lks. west of corner to sections 17-18-19
and 20 which is a post 4 x 4 ins. marked Tp. 2 N. R. 11 W.
section 17 on N. E. S. 20 on S. E. S. 19 on S. W. and
Section 18 on N. W. faces firmly set in large mound of
rocks
Thence I run
S. 0°11' west on a true line between sections 19 and 20
with same variation.
Descend.
8.60 West fork of San Gabriel river 35 lks. wide course east
in timbered ravine 160 lks. wide course east and ascend.
23.50 Point of spur bears N. E. and descend.
40.14 Set granite stone 13 x 11 x 7 ins. 8 ins. in the ground
for 1/4 section corner marked 1/4 on W. face and raised
mound of stone alongside.
Pits impracticable.
80.28 The corner to sections 19-20-29 and 30
Land mountains.
Soil 3rd rate.
Timber Pine and Oak in Canon.
Dense undergrowth of Chaparral.

April 23rd 1884

GENERAL DESCRIPTION

This township contains all mountain land. The soil
classes mostly as 3rd rate.
A large body of Pine timber of fine quality is situate
in sections 27-28-33 and 34 and more or less Pine and Oak
in ravines.
The west fork of San Gabriel river runs through the
township from west to east near the center its general
course being east. The township is generally valuable for
its timber.
